




MICROPLUG - RIGHELLO



MICROPLUG / RIGHELLO

Designed by LITEQ


SIMES


Marine grade stainless steel AISI 316L front trim 3 mm thick.
 Zinc alloy back-ring.
 Polycarbonate housing.
 Methacrylate diffuser.
 Luminaire hard wired with H07RN-F cable, connector and heat resistant sheaths.
 Recessing boxes (for wall recessing) included.
L.E.D circuit included.
 GLOW WIRE TEST: 850°C
 IP65
 CLASS II 
 IK09




Private house, Brescia, Italy © Gianattilio Valli

FINISHING:

 Stainless steel (code 19)



Luminaire supplied with recessing box and cable.
 Wiring must be done outside the fitting.



LED BLUE available on request





All RIGHELLO luminaires are supplied with two clips that allow an easy installation for floating walls and ceiling mounting.
 NOTE: Wall thickness must be between 5 and 30 mm

RIGHELLO SHORT hole \square 226 x 36 mm
 RIGHELLO LONG hole \square 356 x 36 mm



All MICROPLUG luminaires are supplied with two clips that allow an easy installation for floating walls and ceiling mounting.
 NOTE: Wall thickness must be between 5 and 20 mm



Diameter of the hole must be:
 MICROPLUG ROUND \emptyset 60 mm
 MICROPLUG SQUARE \square 60 mm
 MICROPLUG RECTANGULAR \square 57x94 mm




S.4570.19 
With leds white 6000K
Rated luminaire luminous flux 40lm

S.4570W.19 
With leds white 3200K
Rated luminaire luminous flux 28lm

Rated input power 1W 230V





24V d.c. LED versions are available on request




S.4580.19 
With leds white 6000K
Rated luminaire luminous flux 40lm

S.4580W.19 
With leds white 3200K
Rated luminaire luminous flux 28lm

Rated input power 1W 230V





24V d.c. LED versions are available on request



S.4590.19 
With leds white 6000K
Rated luminaire luminous flux 40lm


S.4590W.19 
With leds white 3200K
Rated luminaire luminous flux 28lm

Rated input power 1,3W 230V



24V d.c. LED versions are available on request



SHORT VERSION



S.4507.19 
 With leds white 6000K
 Rated luminaire luminous flux 40lm


S.4507W.19 
 With leds white 3200K
 Rated luminaire luminous flux 28lm


Rated input power 1,3W 230V



24V d.c. LED versions are available on request



LONG VERSION



S.4517.19 
 With leds white 6000K
 Rated luminaire luminous flux 80lm

S.4517W.19 
 With leds white 3200K
 Rated luminaire luminous flux 56lm

Rated input power 2,4W 230V



24V d.c. LED versions are available on request



Auckland War Memorial Museum, Auckland, New Zealand © Targetti NZ