




"Cremona Po" shopping center, Cremona, Italy © Giannattilio Valli



Slot

Wall and ceiling effect

High flexibility can be considered one of the main plus of SLOT. Able to ensure functional lighting with excellent light output, SLOT also allow to create more or less marked light accents suitable for variuos applications. The double emission versions house two lamps, each one with its own adjustable reflector and independent control gear.






SLOT ROUND Wall and ceiling effect

Die-cast EN AB-47100 and extruded EN AW-6060 aluminium housing with high corrosion resistance.
Toughened glass diffuser
6mm thick for MICROSLOT,
8mm thick for MINISLOT,
8mm thick for SLOT,
12mm thick for MEGASLOT.
Stainless steel screws.
Luminaire suitable for single grommet (MICROSLOT CEILING).
Luminaire suitable for double grommets (MICROSLOT WALL).
Luminaire suitable for single cable gland (MINISLOT CEILING).
Luminaire hard wired with single neoprene cable with cable gland.
Silicone gaskets.
Double powdered paint.

Colour:

○ Aluminium grey (code 14)

Protection class
IP65

Isolation class
CLASS I ⚡


Mechanical resistance of diffuser
IK 08
IK 09 (MEGASLOT)

Lamp HIT not included.

Leds large beam versions are available on request.
Leds 4000K CRI90 versions are available on request.

For the latest technical information and product updates with LED technology please refer to the official website (www.simes.it)



S.5500


ANTIGLARE LOUVRE

Only for SLOT ROUND with HIT-CRI lamp and 7° beam reflector.



S.3911

WIDE LENS for MINISLOT ROUND

 from 10° to ~37°



S.3912


ELLIPSOIDAL LENS for MINISLOT ROUND

 from 10° to ~14°x48°



S.3901


WIDE LENS for SLOT ROUND

 from 14° to ~53°



S.3902


ELLIPSOIDAL LENS for SLOT ROUND

 from 7° to ~8°x42°



S.3981


WIDE LENS for MEGASLOT ROUND

 from 16° to ~49°





S.3980

ELLIPSOIDAL LENS for MEGASLOT ROUND

 from 8° to ~8°x40°

Ceiling





S.3905W □

With 3 leds white **3000K** CRI90 425lm
 Rated luminaire luminous flux 288lm
 Rated input power 6W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	33° Ø(m)	3000K E(lx)
1	0.58	796
2	1.17	199
3	1.75	88
4	2.34	50
5	2.92	32

Wall single emission





S.3903W □

With 3 leds white **3000K** CRI90 425lm
 Rated luminaire luminous flux 327lm
 Rated input power 6W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	9° Ø(m)	3000K E(lx)
1	0.16	7297
2	0.33	1824
3	0.49	811
4	0.66	456
5	0.82	292

Wall double emission





S.3913W □

With 6 leds white **3000K** CRI90 850lm
 Rated luminaire luminous flux 654lm
 Rated input power 12W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	9° Ø(m)	3000K E(lx)
1	0.16	7297
2	0.33	1824
3	0.49	811
4	0.66	456
5	0.82	292


Ceiling



S.3957W

With leds white **3000K** CRI90 1180lm
 Rated luminaire luminous flux 781lm
 Rated input power 16W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	39° Ø(m)	3000K E(lx)
1	0.70	1562
2	1.40	391
3	2.10	174
4	2.80	98
5	3.50	62





S.3922

For lamp HIT-TC CRI 35W G8,5 3300lm
 Rated luminaire luminous flux 1551lm
 Rated input power 46W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	10° Ø(m)	E(lx)
2	0.36	3952
4	0.73	988
6	1.09	439
8	1.46	247
10	1.82	158


Wall single emission



S.3950W

With leds white **3000K** CRI90 1180lm
 Rated luminaire luminous flux 834lm
 Rated input power 16W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	28° Ø(m)	3000K E(lx)
2	1.00	833
4	2.01	208
6	3.01	93
8	4.02	52
10	5.02	33





S.3932

For lamp HIT-TC CRI 35W G8,5 3300lm
 Rated luminaire luminous flux 1551lm
 Rated input power 46W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	10° Ø(m)	E(lx)
2	0.36	3952
4	0.73	988
6	1.09	439
8	1.46	247
10	1.82	158


Wall double emission



S.3952W

With leds white **3000K** CRI90 2360lm
 Rated luminaire luminous flux 1668lm
 Rated input power 32W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	28° Ø(m)	3000K E(lx)
2	1.00	833
4	2.01	208
6	3.01	93
8	4.02	52
10	5.02	33





S.3942

For 2 lamps HIT-TC CRI 35W G8,5 3300lm
 Rated luminaire luminous flux 3102lm
 Rated input power 92W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	10° Ø(m)	E(lx)
2	0.36	3952
4	0.73	988
6	1.09	439
8	1.46	247
10	1.82	158


Ceiling



S.3967W □

With leds white **3000K** CRI90 2125lm
 Rated luminaire luminous flux 1280lm
 Rated input power 27W 230V
 Adjustable ±15° optic

h(m)	39° Ø(m)	3000K E(lx)
2	1.43	610
4	2.86	153
6	4.30	68
8	5.73	38
10	7.16	24





S.3926 □

For lamp HIT-CRI 70W G12 6600lm
 Rated luminaire luminous flux 3168lm
 Rated input power 84W 230V
 (7° beam reflector on request)
 Adjustable ±15° optic

h(m)	7° Ø(m)	E(lx)	14° Ø(m)	E(lx)
2	0.28	23744	0.48	3350
4	0.56	5936	0.97	837
6	0.84	2638	1.45	372
8	1.12	1484	1.94	209
10	1.40	950	2.42	134


Wall single emission



S.3960W □

With leds white **3000K** CRI90 2125lm
 Rated luminaire luminous flux 1332lm
 Rated input power 27W 230V
 Adjustable ±15° optic

h(m)	29° Ø(m)	3000K E(lx)
2	1.06	1243
4	2.11	311
6	3.17	138
8	4.23	78
10	5.28	50





S.3936 □

For lamp HIT-CRI 70W G12 6600lm
 Rated luminaire luminous flux 3168lm
 Rated input power 84W 230V
 (7° beam reflector on request)
 Adjustable ±15° optic

h(m)	7° Ø(m)	E(lx)	14° Ø(m)	E(lx)
2	0.28	23744	0.48	3350
4	0.56	5936	0.97	837
6	0.84	2638	1.45	372
8	1.12	1484	1.94	209
10	1.40	950	2.42	134


Wall double emission



S.3962W □

With leds white **3000K** CRI90 4248lm
 Rated luminaire luminous flux 2664lm
 Rated input power 54W 230V
 Adjustable ±15° optic

h(m)	29° Ø(m)	3000K E(lx)
2	1.06	1243
4	2.11	311
6	3.17	138
8	4.23	78
10	5.28	50




S.3946 □

For 2 lamps HIT-CRI 70W G12 6600lm
 Rated luminaire luminous flux 6336lm
 Rated input power 168W 230V
 (7° beam reflectors on request)
 Adjustable ±15° optic

h(m)	7° Ø(m)	E(lx)	14° Ø(m)	E(lx)
2	0.28	23744	0.48	3350
4	0.56	5936	0.97	837
6	0.84	2638	1.45	372
8	1.12	1484	1.94	209
10	1.40	950	2.42	134

Ceiling



∅ 250





S.3929

For lamp HIT-CRI 150W G12 14000lm
 Rated luminaire luminous flux 8400lm
 Rated input power 149W 230V
 (8° beam reflector on request)
 Adjustable ±15° optic

h(m)	∅(m)	8°		16°	
		E(lx)	∅(m)	E(lx)	∅(m)
4	0.53	12913	1.00	3545	
8	1.06	3228	1.99	886	
12	1.59	1435	2.99	394	
16	2.13	807	3.99	222	
20	2.66	517	4.98	142	

Wall single emission



∅ 250





S.3939


For lamp HIT-CRI 150W G12 14000lm
 Rated luminaire luminous flux 8400lm
 Rated input power 149W 230V
 (8° beam reflector on request)
 Adjustable ±15° optic

h(m)	∅(m)	8°		16°	
		E(lx)	∅(m)	E(lx)	∅(m)
4	0.53	12913	1.00	3545	
8	1.06	3228	1.99	886	
12	1.59	1435	2.99	394	
16	2.13	807	3.99	222	
20	2.66	517	4.98	142	

Wall double emission



∅ 250



S.3949

For 2 lamps HIT-CRI 150W G12 14000lm
 Rated luminaire luminous flux 16800lm
 Rated input power 298W 230V
 (8° beam reflectors on request)
 Adjustable ±15° optic

h(m)	∅(m)	8°		16°	
		E(lx)	∅(m)	E(lx)	∅(m)
4	0.53	12913	1.00	3545	
8	1.06	3228	1.99	886	
12	1.59	1435	2.99	394	
16	2.13	807	3.99	222	
20	2.66	517	4.98	142	





Palace music hall, Thessaloniki, Greece © Gravani Lighting

SLOT SQUARE Wall and ceiling effect

Die-cast EN AB-47100 and extruded EN AW-6060 aluminium housing with high corrosion resistance.
Toughened glass diffuser
6mm thick for MICROSLOT,
8mm thick for MINISLOT,
8mm thick for SLOT.
Stainless steel screws.
Luminaire suitable for single grommet (MICROSLOT CEILING).
Luminaire suitable for double grommets (MICROSLOT WALL).
Luminaire suitable for double grommets.
Silicone gaskets.
Double powdered paint.

Colour:

○ Aluminium grey (code 14)

Protection class

IP65

Isolation class

CLASS I ⊕

Mechanical resistance of diffuser

IK 08

Lamp HIT not included.

Leds large beam versions are available on request.
Leds 4000K CRI90 versions are available on request.

For the latest technical information and product updates with LED technology please refer to the official website (www.simes.it)



S.3811

EXTENSIVE LENS for MINISLOT SQUARE

➤ from 28° to ~38°



S.3812

ELLIPSOIDAL LENS for MINISLOT SQUARE

➤ from 10° to ~12°x65°



S.3801

EXTENSIVE LENS for SLOT SQUARE

➤ from 30° to ~43°





S.3802

ELLIPSOIDAL LENS for SLOT SQUARE

➤ from 10° to ~12°x60°



Ceiling



S.3805W □
 With 3 leds white **3000K** CRI90 425lm
 Rated luminaire luminous flux 288lm
 Rated input power 6W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	33° Ø(m)	3000K E(lx)
1	0.58	796
2	1.17	199
3	1.75	88
4	2.34	50
5	2.92	32



Wall single emission



S.3803W □
 With 3 leds white **3000K** CRI90 425lm
 Rated luminaire luminous flux 327lm
 Rated input power 6W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	9° Ø(m)	3000K E(lx)
1	0.16	7297
2	0.33	1824
3	0.49	811
4	0.66	456
5	0.82	292



Wall double emission



S.3813W □
 With 6 leds white **3000K** CRI90 850lm
 Rated luminaire luminous flux 654lm
 Rated input power 12W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	9° Ø(m)	3000K E(lx)
1	0.16	7297
2	0.33	1824
3	0.49	811
4	0.66	456
5	0.82	292


Ceiling



S.3857W

With leds white **3000K** CRI90 1180lm
 Rated luminaire luminous flux 781lm
 Rated input power 16W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	39° Ø(m)	3000K E(lx)
1	0.70	1562
2	1.40	391
3	2.10	174
4	2.80	98
5	3.50	62





S.3822

For lamp HIT-TC CRI 35W G8,5 3300lm
 Rated luminaire luminous flux 2013lm
 Rated input power 46W 230V
 (9° beam reflector on request)
 Adjustable $\pm 15^\circ$ optic

h(m)	9° Ø(m)	26° E(lx) Ø(m)	E(lx)
2	0.32	9810 0.94	1981
4	0.64	2453 1.88	495
6	0.97	1090 2.81	220
8	1.29	613 3.75	124
10	1.61	392 4.69	79


Wall single emission



S.3850W

With leds white **3000K** CRI90 1180lm
 Rated luminaire luminous flux 834lm
 Rated input power 16W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	28° Ø(m)	3000K E(lx)
2	1.00	833
4	2.01	208
6	3.01	93
8	4.02	52
10	5.02	33





S.3832

For lamp HIT-TC CRI 35W G8,5 3300lm
 Rated luminaire luminous flux 2013lm
 Rated input power 46W 230V
 (9° beam reflector on request)
 Adjustable $\pm 15^\circ$ optic

h(m)	9° Ø(m)	26° E(lx) Ø(m)	E(lx)
2	0.32	9810 0.94	1981
4	0.64	2453 1.88	495
6	0.97	1090 2.81	220
8	1.29	613 3.75	124
10	1.61	392 4.69	79


Wall double emission



S.3852W

With leds white **3000K** CRI90 2360lm
 Rated luminaire luminous flux 1668lm
 Rated input power 32W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	28° Ø(m)	3000K E(lx)
2	1.00	833
4	2.01	208
6	3.01	93
8	4.02	52
10	5.02	33






S.3842

For 2 lamps HIT-TC CRI 35W G8,5 3300lm
 Rated luminaire luminous flux 4026lm
 Rated input power 92W 230V
 (9° beam reflector on request)
 Adjustable $\pm 15^\circ$ optic

h(m)	9° Ø(m)	26° E(lx) Ø(m)	E(lx)
2	0.32	9810 0.94	1981
4	0.64	2453 1.88	495
6	0.97	1090 2.81	220
8	1.29	613 3.75	124
10	1.61	392 4.69	79


Ceiling




S.3867W 

With leds white **3000K** CRI90 2125lm
 Rated luminaire luminous flux 1280lm
 Rated input power 27W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	39°	
	Ø(m)	3000K E(lx)
2	1.43	610
4	2.86	153
6	4.30	68
8	5.73	38
10	7.16	24






S.3826 

For lamp HIT-CRI 70W G12 6600lm
 Rated luminaire luminous flux 3234lm
 Rated input power 84W 230V
 (10° beam reflector on request)
 Adjustable $\pm 15^\circ$ optic

h(m)	10°		33°	
	Ø(m)	E(lx)	Ø(m)	E(lx)
2	0.35	11644	1.18	1752
4	0.70	2911	2.35	438
6	1.05	1294	3.53	195
8	1.40	728	4.71	109
10	1.75	466	5.89	70


Wall single emission



S.3860W 

With leds white **3000K** CRI90 2125lm
 Rated luminaire luminous flux 1332lm
 Rated input power 27W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	29°	
	Ø(m)	3000K E(lx)
2	1.06	1243
4	2.11	311
6	3.17	138
8	4.23	78
10	5.28	50






S.3836 

For lamp HIT-CRI 70W G12 6600lm
 Rated luminaire luminous flux 3234lm
 Rated input power 84W 230V
 (10° beam reflector on request)
 Adjustable $\pm 15^\circ$ optic

h(m)	10°		33°	
	Ø(m)	E(lx)	Ø(m)	E(lx)
2	0.35	11644	1.18	1752
4	0.70	2911	2.35	438
6	1.05	1294	3.53	195
8	1.40	728	4.71	109
10	1.75	466	5.89	70


Wall double emission



S.3862W 

With leds white **3000K** CRI90 4248lm
 Rated luminaire luminous flux 2664lm
 Rated input power 54W 230V
 Adjustable $\pm 15^\circ$ optic

h(m)	29°	
	Ø(m)	3000K E(lx)
2	1.06	1243
4	2.11	311
6	3.17	138
8	4.23	78
10	5.28	50



S.3846 

For 2 lamps HIT-CRI 70W G12 6600lm
 Rated luminaire luminous flux 6468lm
 Rated input power 168W 230V
 (10° beam reflectors on request)
 Adjustable $\pm 15^\circ$ optic

h(m)	10°		33°	
	Ø(m)	E(lx)	Ø(m)	E(lx)
2	0.35	11644	1.18	1752
4	0.70	2911	2.35	438
6	1.05	1294	3.53	195
8	1.40	728	4.71	109
10	1.75	466	5.89	70



"Nanni Member" car dealer, Brescia, Italy © Giannattilio Valli

