






Zip Downlight comfort

Recessed

ZIP DOWNLIGHT is a range of ceiling-recessed light fittings available in square and round versions, supplied with new-generation comfort optics. This range of luminaires is the right answer to any architectural need, both functional lighting and accent lighting.





Virgin Active, Brescia, Arch. Franco Scaglia © Ottavio Tomasini

ZIP DOWNLIGHT COMFORT Recessed

Die-cast EN AB-44100 aluminium housing with high corrosion resistance. Marine grade stainless steel AISI 316L front trim 2 mm thick. Toughened glass diffuser 8mm thick for MICROZIP, 8mm thick for MINIZIP, 10mm thick for ZIP, 12mm thick for MEGAZIP. Stainless steel screws. Luminaire supplied with 1,5m of cable (Microzip). Luminaire with one single cable entry and cable gland (Minizip). Luminaire with double cable entry and cable glands (Zip and Megazip). Silicone gaskets.
Double powder paint.

Finishing:

○ Stainless steel (code 19)

Protection class
IP65

Isolation class
CLASS I ⊕

Mechanical resistance
IK 09

For the latest technical information and luminaire updates with LED technology please refer to www.simes.it




RECESSING box for installation in concrete ceilings.

S.5512 MICROZIP ROUND
Dimensions: Ø 80÷124 mm h 125 mm

S.5510 MINIZIP ROUND
Dimensions: Ø 121÷165 mm h 135 mm

S.5520 ZIP ROUND
Dimensions: Ø 190 mm h 240 mm

S.5530 MEGAZIP ROUND
Dimensions: Ø 260 mm h 245 mm



RECESSING box for installation in concrete ceilings.



S.5516 MICROZIP SQUARE
Dimensions: 80÷124 mm h 125 mm

S.5511 MINIZIP SQUARE
Dimensions: 121÷165 mm h 135 mm


S.5521 ZIP SQUARE
Dimensions: 190 mm h 240 mm

S.5531 MEGAZIP SQUARE
Dimensions: 260 mm h 245 mm

Semiacid - etched glass



S.5515W.19 
 1 HIGH-POWER LED **3000K** CRI90 105lm
 Rated luminaire luminous flux 91lm



S.5515N.19 
 1 HIGH-POWER LED **4000K** CRI90 115lm
 Rated luminaire luminous flux 98lm


Rated input power 2,2W
 220V-230V AC 50/60Hz / DC Not Dimmable
 Adjustable $\pm 15^\circ$ optic

**Beam lenses available on request with no surcharge:
 12° and 26°**

h(m)	38° Ø(m)	3000K E(lx)	4000K E(lx)
1	0.69	191	206
2	1.39	48	52
3	2.08	21	23
4	2.77	12	13
5	3.46	8	8

Semiacid - etched glass



S.5525W.19 
 1 HIGH-POWER LED **3000K** CRI90 105lm
 Rated luminaire luminous flux 91lm

S.5525N.19 
 1 HIGH-POWER LED **4000K** CRI90 115lm
 Rated luminaire luminous flux 98lm



Rated input power 2,2W
 220V-230V AC 50/60Hz / DC Not Dimmable
 Adjustable $\pm 15^\circ$ optic


**Beam lenses available on request with no surcharge:
 12° and 26°**

h(m)	38° Ø(m)	3000K E(lx)	4000K E(lx)
1	0.69	191	206
2	1.39	48	52
3	2.08	21	23
4	2.77	12	13
5	3.46	8	8

MINIZIP DOWNLIGHT COMFORT

Semiacid - etched glass





S.5545W.19 
 1 COB LED **3000K** CRI90 350lm
 Rated luminaire luminous flux 284lm


S.5545N.19 
 1 COB LED **4000K** CRI90 360lm
 Rated luminaire luminous flux 292lm

Rated input power 4,3W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable $\pm 15^\circ$ optic
 Computer-simulated photometrics

h(m)	33° Ø(m)	3000K E(lx)	4000K E(lx)
1	0.62	643	656
2	1.23	161	164
3	1.85	71	73
4	2.46	40	41
5	3.08	26	26

Semiacid - etched glass



S.5555W.19 
 1 COB LED **3000K** CRI90 350lm
 Rated luminaire luminous flux 284lm

S.5555N.19 
 1 COB LED **4000K** CRI90 360lm
 Rated luminaire luminous flux 292lm


Rated input power 4,3W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable $\pm 15^\circ$ optic
 Computer-simulated photometrics

h(m)	33° Ø(m)	3000K E(lx)	4000K E(lx)
1	0.62	643	656
2	1.23	161	164
3	1.85	71	73
4	2.46	40	41
5	3.08	26	26

ZIP DOWNLIGHT COMFORT

SIMES


Semiacid - etched glass



S.5565W.19
 1 COB LED **3000K** CRI90 1470lm
 Rated luminaire luminous flux 1029lm


S.5565N.19
 1 COB LED **4000K** CRI90 1520lm
 Rated luminaire luminous flux 1064m

h(m)	33° Ø(m)	3000K E(lx)	4000K E(lx)
1	0.49	3419	3522
2	0.98	855	881
3	1.46	380	391
4	1.95	214	220
5	2.44	137	141



Rated input power 14W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable ±15° optic
 Computer-simulated photometrics


Semiacid - etched glass



S.5575W.19
 1 COB LED **3000K** CRI90 1470lm
 Rated luminaire luminous flux 1029lm

S.5575N.19
 1 COB LED **4000K** CRI90 1520lm
 Rated luminaire luminous flux 1064m


h(m)	33° Ø(m)	3000K E(lx)	4000K E(lx)
1	0.49	3419	3522
2	0.98	855	881
3	1.46	380	391
4	1.95	214	220
5	2.44	137	141



Rated input power 14W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable ±15° optic
 Computer-simulated photometrics

MEGAZIP DOWNLIGHT COMFORT


Semiacid - etched glass



S.5585W.19
 1 COB LED **3000K** CRI90 2950lm
 Rated luminaire luminous flux 2061lm


S.5585N.19
 1 COB LED **4000K** CRI90 3038lm
 Rated luminaire luminous flux 2126lm

h(m)	33° Ø(m)	3000K E(lx)	4000K E(lx)
2	1.06	1814	1868
4	2.11	453	467
6	3.17	202	208
8	4.23	113	117
10	5.28	73	75



Rated input power 28W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable ±15° optic
 Computer-simulated photometrics


Semiacid - etched glass



S.5595W.19
 1 COB LED **3000K** CRI90 2950lm
 Rated luminaire luminous flux 2061lm

S.5595N.19
 1 COB LED **4000K** CRI90 3038lm
 Rated luminaire luminous flux 2126lm

h(m)	33° Ø(m)	3000K E(lx)	4000K E(lx)
2	1.06	1814	1868
4	2.11	453	467
6	3.17	202	208
8	4.23	113	117
10	5.28	73	75



Rated input power 28W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable ±15° optic
 Computer-simulated photometrics

