


## ACCESSORY



### S.2815 CYLINDRICAL POLEH 6,44m Ø102mm TO BE BURIED

Cylindrical shaped poles consisting of: straight circular section shaft,  $\varnothing 102$ mm, 4mm in thickness, total length 7,24m , single section built by using longitudinally welded tubes by induction welding (ERW) UNI EN 10219-2-ISO 4200

Suitable for ground recessed installation to a cement base 0,80m  
: Suggested reinforced concrete footstall dimension 1,0m x 1,0m  
h 1m. Footstall dimension can be calculated according to your country norms and ground properties.

The grade of steel used is S235JR (Fe360B) with material characteristics as per normative UNI EN 10025;

The surface protection treatment is done through hot dip galvanization.

Painting Process: PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions. Resistance test protection for Marine applications for 1500h.

Including inspection door, terminal cable block and fuse.

WE RECOMMEND THE USE OF THE FOLLOWING  
ACCESSORIES :  
S.2809 POLE BASE COVER

Accessory available in the following colors: Anthracite grey  
(cod.24)