





Concrete up-light

The result of continuous research on new technology embraces the essence of LED. Without the need of a recessing box and a limited height the up lighter is the perfect expression of contemporary light. A high performance luminaire in a simple form for easy installation that is able to redefine the concept of ground recessed fixtures.





Concrete covering with added synthetic fibers with high mechanical strength.
 Die cast EN AB-47100 aluminium (low copper content) housing with high corrosion resistance.
 Reflector in polymers covered with 99.98% pure aluminium
 Toughened glass diffuser.
 Stainless steel screws.
 Luminaire hard wired 3m with single neoprene cable.
 Silicone gaskets.
 Supplied with ground fixing base.

Protection class
 IP67

Isolation class
 CLASS I ⊕

Mechanical resistance of glass
 IK 06

Leds 4000K CRI90 versions are available on request.


REGISTERED DESIGN

This product has been manufactured with hand crafted procedures, therefore small imperfections, subsidence of the concrete surface, actual cracks and future, colour ripples and variations over time, are deliberately present and they are a feature of the concrete product, proving the hand-made manufacturing procedure.

For the latest technical information and product updates with LED technology please refer to the official website (www.simes.it)


Colours:

- Concrete (cod. 35)




C.8150W.35
 With COB led white **3000K** CRI83 800lm
 Rated luminaire luminous flux 650lm
 Rated input power 13W 230V

h(m)	E(lx) 3000K	17°
10.0	0.5	
8.0	1.0	
6.0	2.0	
4.0	6.0	
2.0	43.0	
0.1 m	0(m)	



C.8155W.35
 With COB led white **3000K** CRI83 2000lm
 Rated luminaire luminous flux 1700lm
 Rated input power 26,2W 230V

h(m)	E(lx) 3000K	24°
10.0	1.0	
8.0	1.5	
6.0	3.0	
4.0	9.0	
2.0	67.0	
0.1 m	0(m)	



Ground stake accessory for garden installation



S.3524
STAKE in polypropilene.
 Colour: black (code 09)
 Length 270 mm