

Cool is a simple void volume that diffuses indirect light through a very thin circuit placed in adherence to the glass that protects it. Designed in different versions and sizes, wall or bollard, the Cool family offers a new way to illuminate the exterior, drawing real "solid and voids of light".

TECHNICAL DESCRIPTION

Die-cast aluminium housing, extruded aluminium structure (bollard version) with high corrosion resistance. Toughened glass diffuser. Stainless steel A4 screws. Silicone gaskets. Double powder paint.

MINICOOL L 220mm

Luminaire supplied with 1,0m neoprene H05RN-F cable.

MINICOOL L 220mm BOLLARD

Luminaire supplied with neoprene H05RN-F cable and connector.

COOL L 290mm APPLIQUE

Luminaire with one single cable entry and grommet.

COOL L 290mm BOLLARD

Luminaire supplied with neoprene H05RN-F cable and connector.

REGISTERED DESIGN

PROTECTION CLASS
IP54

ISOLATION CLASS

CLASS II ☐ MINICOOL L 220 mm
CLASS I ⊕ COOL L 290 mm

MECHANICAL RESISTANCE

IK 06



COLOURS

.01 White

.09 Black

.14 Aluminium Grey




www.simes.it/cool

MINICOOL 220mm


SIMES

Minicool Applique 220mm




S.7231W

LED MODULE **3000K** CRI90 1313lm 11,1W
 (on request 2700K CRI90 1247lm)
 (on request 4000K CRI80 1751lm)
 220V-230Vac 50/60Hz
 ON/OFF Not Dimmable




Minicool Bollard H 220mm




S.7236W

LED MODULE **3000K** CRI90 1313lm 11,1W
 (on request 2700K CRI90 1247lm)
 (on request 4000K CRI80 1751lm)
 220V-230Vac 50/60Hz
 ON/OFF Not Dimmable




Minicool Bollard H 580mm



S.7241W

LED MODULE **3000K** CRI90 1313lm 11,1W
 (on request 2700K CRI90 1247lm)
 (on request 4000K CRI80 1751lm)
 220V-230Vac 50/60Hz
 ON/OFF Not Dimmable



Accessory




S.7249

FLANGE FOR MINICOOL BOLLARD
 flange to be anchored in concrete
 for S.7236W and S.7241W




Cool Applique 290mm




S.7270W

LED MODULE **3000K** CRI90 2100lm 17,8W
 (on request 2700K CRI90 1995lm)
 (on request 4000K CRI80 2801lm)
 220V-240Vac 50/60Hz
Phase-cut dimmer




Version with DALI 2 / PUSH power supply available on request with surcharge.

Cool Bollard H 290mm




S.7245W

LED MODULE **3000K** CRI90 2100lm 17,8W
 (on request 2700K CRI90 1995lm)
 (on request 4000K CRI80 2801lm)
 220V-240Vac 50/60Hz
Phase-cut dimmer




Version with DALI 2 / PUSH power supply available on request with surcharge.

Cool Bollard H 580mm



S.7246W

LED MODULE **3000K** CRI90 2100lm 17,8W
 (on request 2700K CRI90 1995lm)
 (on request 4000K CRI80 2801lm)
 220V-240Vac 50/60Hz
Phase-cut dimmer



Version with DALI 2 / PUSH power supply available on request with surcharge.



Accessory

S.7269

FLANGE FOR COOL BOLLARD
 Flange to be anchored in concrete for S.7245W and S.7246W



Private villa, Forte dei Marmi, Lucca, Italy - Arch. Carlo Ceresoli © ph. Mauro Pini