




Lovato electric headquarter, Gorle, (Bergamo), Italy © ph. Gianmattio Valli



Cubiks

Bollard

CUBIKS is a range of bollards with a minimalistic and clean-cut design, suitable for the illumination of areas in modern urban context. CUBIKS is totally glare-free and provides extremely uniform light distribution on the ground. The clean, essential design of this bollard makes its installation perfect in high profile architectural projects.





CUBIKS Bollard

Die-cast EN AB-47100 and extruded EN AW-6060 aluminium housing with high corrosion resistance.

Reflector in polymers covered with 99.98% pure aluminium (Cubiks and Megacubiks).

Clear polycarbonate reeded diffuser.

Stainless steel screws.

Pre-wired luminaire with neoprene cable and connector.

Silicone gaskets.

Double powder paint.

Protection class

IP65 MINICUBIKS

IP66 CUBIKS and MEGACUBIKS

Isolation class

CLASS II 

Mechanical resistance of glass

IK 10

Leds 4000K CRI90 versions are available on request.




S.5506

4 way connector for through wiring (in/out).



For the latest technical information and luminaire updates with LED technology please refer to www.simes.it

Colour:

 Aluminium grey (code 14)


REGISTERED DESIGN

H 550 mm



S.5314W

4 HIGH-POWER LEDs **3000K** CRI90 760lm
 Rated luminaire luminous flux 127lm
 Rated input power 11W
 220V-240V AC 50/60Hz / DC Not Dimmable



Ø 120





S.6309

FLANGE ACCESSORY FOR MINICUBIKS

Ø 120 mm flange to be buried in concrete with stainless steel screws for fixing in the ground.


CUBIKS

H 350 mm





S.5334W

4 COB LEDs **3000K** CRI90 4500lm
 Rated luminaire luminous flux 1530lm
 Rated input power 40W
 220V-240V AC 50/60Hz / DC Not Dimmable




H 800 mm



S.5339W

4 COB LEDs **3000K** CRI90 4500lm
 Rated luminaire luminous flux 1530lm
 Rated input power 40W
 220V-240V AC 50/60Hz / DC Not Dimmable



Ø 180




S.5310

FLANGE ACCESSORY FOR CUBIKS


Ø 180 mm flange to be fixed in concrete with stainless steel screws for fixing in the ground.

H 450 mm




240 x 240

450




S.5374W 

4 COB LEDs **3000K** CRI90 5900lm
 Rated luminaire luminous flux 2120lm
 Rated input power 55W
 220V-240V AC 50/60Hz / DC Not Dimmable




H 950 mm




240 x 240

950



S.5379W 

4 COB LEDs **3000K** CRI90 5900lm
 Rated luminaire luminous flux 2120lm
 Rated input power 55W
 220V-240V AC 50/60Hz / DC Not Dimmable



Ø 240



S.5350

FLANGE ACCESSORY FOR MEGACUBIKS

Ø 240 mm flange to be fixed in concrete with stainless steel screws for fixing in the ground.

