


Lift

Wall effect

Wall effect of a rigorous geometry design, LIFT fits perfectly in different architectural environments personalizing any context in a clear way.





"Elpidia" children's hospital, Athens, Greece © Gravani Bros SA

LIFT Wall effect

Die-cast EN AB-47100 aluminium housing with high corrosion resistance.
Reflector in polymers covered with 99.98% pure aluminium.
Clear toughened glass.
Stainless steel screws.
Luminaire with one single cable entry and grommet (Minilift).
Luminaire with double cable entry and cable glands (Lift).
Silicone gaskets.
Double powder paint.

Protection class

IP65

Isolation class

CLASS II  MINILIFT

CLASS I  LIFT


Mechanical resistance of glass

IK 06

Leds 4000K CR170 versions are available on request.


For the latest technical information and luminaire updates with LED technology please refer to www.simes.it

Colours:

 Aluminium grey (code 14)



REGISTERED DESIGN

1 wide beam




S.5077W

1 HIGH-POWER LED **3000K** CRI80 170lm
 Rated luminaire luminous flux 38lm
 Rated input power 3,5W
 220V-240V AC 50/60Hz / DC Not Dimmable





1 narrow beam




S.5067W

1 HIGH-POWER LED **3000K** CRI80 170lm
 Rated luminaire luminous flux 20lm
 Rated input power 3,5W
 220V-240V AC 50/60Hz / DC Not Dimmable





2 wide beams




S.5027W

2 HIGH-POWER LEDs **3000K** CRI80 340lm
 Rated luminaire luminous flux 76lm
 Rated input power 6,5W
 220V-240V AC 50/60Hz / DC Not Dimmable





1 wide beam + 1 narrow beam




S.5037W

2 HIGH-POWER LEDs **3000K** CRI80 340lm
 Rated luminaire luminous flux 58lm
 Rated input power 6,5W
 220V-240V AC 50/60Hz / DC Not Dimmable





2 narrow beams




S.5047W □

2 HIGH-POWER LEDs **3000K** CRI80 340lm
 Rated luminaire luminous flux 40lm
 Rated input power 6,5W
 220V-240V AC 50/60Hz / DC Not Dimmable





4 narrow beams




S.5087W □

4 HIGH-POWER LEDs **3000K** CRI80 680lm
 Rated luminaire luminous flux 80lm
 Rated input power 11,4W
 220V-240V AC 50/60Hz / DC Not Dimmable





4 wide beams




S.5097W □

4 HIGH-POWER LEDs **3000K** CRI80 680lm
 Rated luminaire luminous flux 152lm
 Rated input power 11,4W
 220V-240V AC 50/60Hz / DC Not Dimmable







1 wide beam




S.5070W

1 COB LED **3000K** CRI90 1850lm
 Rated luminaire luminous flux 202lm
 Rated input power 18,2W
 220V-240V AC 50/60Hz / DC Not Dimmable





1 narrow beam




S.5075W

1 COB LED **3000K** CRI90 1850lm
 Rated luminaire luminous flux 109lm
 Rated input power 18,2W
 220V-240V AC 50/60Hz / DC Not Dimmable





2 wide beams




S.5026W

1 COB LED **3000K** CRI90 1850lm
 Rated luminaire luminous flux 404lm
 Rated input power 18,2W
 220V-240V AC 50/60Hz / DC Not Dimmable





1 wide beam + 1 narrow beam





S.5033W

1 COB LED **3000K** CRI90 1850lm
 Rated luminaire luminous flux 311lm
 Rated input power 18,2W
 220V-240V AC 50/60Hz / DC Not Dimmable





2 narrow beams




S.5040W

1 COB LED **3000K** CRI90 1850lm
 Rated luminaire luminous flux 218lm
 Rated input power 18,2W
 220V-240V AC 50/60Hz / DC Not Dimmable





4 narrow beams




S.5080W

1 COB LED **3000K** CRI90 1850lm
 Rated luminaire luminous flux 436lm
 Rated input power 18,2W
 220V-240V AC 50/60Hz / DC Not Dimmable





4 wide beams



S.5090W

1 COB LED **3000K** CRI90 1850lm
 Rated luminaire luminous flux 808lm
 Rated input power 18,2W
 220V-240V AC 50/60Hz / DC Not Dimmable





Municipality of Semily, Czech Republic © Exx s.r.o.

LIFT RECTANGULAR Wall effect

Die-cast EN AB-47100 aluminium housing with high corrosion resistance.
Acid-etched toughened glass.
Stainless steel screws.
Luminaire with double cable entry and cable glands
Silicone gaskets.
Double powder paint.

Protection class
IP65

Isolation class
CLASS I ⊕

Mechanical resistance of glass
IK 06

Leds 4000K CRI90 versions are available on request.

Colours:

○ Aluminium grey (code 14)

For the latest technical information and luminaire updates with LED technology please refer to www.simes.it