




Linear frame

LINEAR FRAME is a linear fitting for façade lighting effects; it provides soft illumination with a wide and uniform distribution. It can be supplied with LED light sources. The minimalist shape of LINEAR FRAME blends into the building without interfering with the architecture.







Aci Valledlunga (ex-Alfa Romeo racetrack), Lainate, Varese, Italy - Arch. Michele de Lucchi © ph. Mario Bertani

LINEAR FRAME

Die-cast EN AB-47100 and extruded EN AW-6060 aluminium housing with high corrosion resistance.
Clear toughened glass diffuser 10 mm thick.
99.98% pure aluminium reflector.
Stainless steel screws.
Luminaire suitable for double cable glands.
Silicone gaskets.
Double powdered paint.

Protection class
IP65

Isolation class
CLASS II 
CLASS III  RGB


Mechanical resistance of diffuser
IK 09

Colour:

Aluminium grey (code 14)

For the latest technical information and product updates with LED technology please refer to the official website (www.simes.it)

Linear 350 mm



S.5972W


With 6 led white **3000K** CRI90 850lm
 Rated luminaire luminous flux 812lm
 Rated input power 11W 230V
 Asymmetric reflector

S.5972N


With 6 led white **4000K** CRI90 920lm
 Rated luminaire luminous flux 877lm
 Rated input power 11W 230V
 Asymmetric reflector

h(m)	E(lx)			
5	1	1	0	0
4	2	2	1	1
3	3	3	3	2
2	13	12	6	4
1	80	60	15	6

h(m)	E(lx)			
5	1	1	0	0
4	2	2	1	1
3	4	3	3	2
2	15	13	7	5
1	58	62	16	7



Linear 950 mm



S.5982W

With 18 led white **3000K** CRI90 2550lm
 Rated luminaire luminous flux 2058lm
 Rated input power 33W 230V
 Asymmetric reflector

S.5982N

With 18 led white **4000K** CRI90 2755lm
 Rated luminaire luminous flux 2223lm
 Rated input power 33W 230V
 Asymmetric reflector

h(m)	E(lx)			
5	2	1	1	1
4	3	3	2	1
3	7	6	3	2
2	24	15	6	2
1	138	41	6	1

h(m)	E(lx)			
5	2	1	1	1
4	3	3	2	2
3	8	7	4	2
2	25	16	7	2
1	160	48	7	1

S.5990

With 36 leds RGB Asymmetric reflector
 Rated input power 32W **24V PWM**
 Requires remote power supply
 230V/24V PWM (type S.3413) and
 DMX control unit (type S.3493)

h(m)	E(lx)			
5	1	1	1	1
4	2	2	2	1
3	6	5	3	2
2	22	14	6	2
1	126	35	5	1

