

Lobby is an outdoor recessed downlight, highly performing, available in two versions: the basic version has an aluminium front ring and visible screws while the professional one has stainless steel front ring and total absence of visible screws. Both versions are engineered with a double optic system composed of a primary optic that uses a satin glass to better distribute the light and a secondary optic that uses an aluminum reflector to avoid the glare. Lobby can be directly installed in plasterboards or with its recessing box, for concrete ceilings.

TECHNICAL DESCRIPTION

Die-cast EN aluminium housing with high corrosion resistance. Marine grade stainless steel AISI 316L front trim 2mm thick or aluminium. Reflector in polymers covered with aluminium. Toughened glass 10 mm thick. Stainless steel A4 screws. Silicone gaskets. Double powder paint.

LOBBY BASIC

Aluminium front trim with visible screws. Luminaire pre-wired with 0,5m neoprene H05RN-F cable and connector for remote connection.

LOBBY PROFESSIONAL

Marine grade stainless steel AISI 316L front trim with interlocking clips system. Luminaire with double cable entry and cable glands.

PROTECTION CLASS
IP65

ISOLATION CLASS
CLASS II ☐

MECHANICAL RESISTANCE
IK 10

FINISHING BASIC


.09 Black

FINISHING PROFESSIONAL

.19 Stainless Steel



PATENTED






S.7309
RECESSING BOX FOR CONCRETE CEILINGS
for MINILOBBY BASIC
 Dim. 200 x 200 x 120mm
 Recessed box in galvanized steel.


Minilobby Aluminium trim



S.7306W Flood beam with reflector
 LED MODULE **3000K** CRI90 955lm 6,5W
 (on request 2700K CRI90 908lm)
 (on request 4000K CRI80 1171lm)
 220V-230Vac 50/60Hz
 ON/OFF Not Dimmable





S.7307W Medium beam with reflector
 LED MODULE **3000K** CRI90 955lm 6,5W
 (on request 2700K CRI90 908lm)
 (on request 4000K CRI80 1171lm)
 220V-230Vac 50/60Hz
 ON/OFF Not Dimmable




S.7349
RECESSING BOX FOR CONCRETE CEILINGS
for MINILOBBY PROFESSIONAL
 Dim. 360 x 200 x 170mm
 Recessed box in galvanized steel.


Minilobby Stainless steel trim



S.7340W.19 Flood beam with reflector
 LED MODULE **3000K** CRI90 1618lm 11,8W
 (on request 2700K CRI90 1538lm)
 (on request 4000K CRI80 1983lm)
 220V-240Vac 50/60Hz
Dimmable DALI 2 / PUSH





S.7345W.19 Medium beam with reflector
 LED MODULE **3000K** CRI90 1618lm 11,8W
 (on request 2700K CRI90 1538lm)
 (on request 4000K CRI80 1983lm)
 220V-240Vac 50/60Hz
Dimmable DALI 2 / PUSH




S.7329
RECESSING BOX FOR CONCRETE CEILINGS
for LOBBY BASIC
 Dim. 260 x 260 x 150mm
 Recessed box in galvanized steel.



Lobby Aluminium trim



S.7326W Very Wide Flood beam with reflector
 LED MODULE **3000K** CRI90 2234lm 17,4W
 (on request 2700K CRI90 2123lm)
 (on request 4000K CRI80 2738lm)
 220V-230Vac 50/60Hz
 ON/OFF Not Dimmable





S.7327W Wide Flood beam with reflector
 LED MODULE **3000K** CRI90 2234lm 17,4W
 (on request 2700K CRI90 2123lm)
 (on request 4000K CRI80 2738lm)
 220V-230Vac 50/60Hz
 ON/OFF Not Dimmable




S.7369
RECESSING BOX FOR CONCRETE CEILINGS
for LOBBY PROFESSIONAL
 Dim. 400 x 260 x 170mm
 Recessed box in galvanized steel.

Lobby Stainless steel trim



S.7360W.19 Very Wide Flood beam with reflector
 LED MODULE **3000K** CRI90 3231lm 24,1W
 (on request 2700K CRI90 3071lm)
 (on request 4000K CRI80 3959lm)
 220V-240Vac 50/60Hz
Dimmable DALI 2 / PUSH



S.7365W.19 Flood beam with reflector
 LED MODULE **3000K** CRI90 3231lm 24,1W
 (on request 2700K CRI90 3071lm)
 (on request 4000K CRI80 3959lm)
 220V-240Vac 50/60Hz
Dimmable DALI 2 / PUSH

