






Loft spot

Adjustable projector

Minimal and essential projector with perfect control of the beam. Glare free and available with narrow and wide beam.





Galleria Arte Moderna, Pordenone, Italy © ph. Elio e Stefano Ciol

LOFT SPOT Adjustable projector

Die-cast EN AB-47100 aluminium housing with high corrosion resistance.
Stainless steel screws.
Clear toughened glass diffuser.
Luminaire hard wired with single neoprene cable (MICROLOFT).
Luminaire suitable for single cable gland.
Silicone gaskets.
Double powdered paint.

Colours:

- White (code .01)
- Aluminium grey (code .14)

For the latest technical information and product updates with LED technology please refer to the official website (www.simes.it)

Protection class

IP65

Isolation class

CLASS I ⊕
CLASS II ⊞ MICROLOFT and MEGALOFT

Mechanical resistance of diffuser

IK 06

Lamp HIT not included.

Leds large beam versions are available on request.
Leds 4000K CR190 versions are available on request.

REGISTERED DESIGN



S.1004

STAKE FOR MINILOFT and LOFT SLIM

In polypropilene
Colour: black (code .09)
The 100 mm upper part must stay out of the ground level, according with the norms.






S.1005

STAKE FOR MEGALOFT SLIM


In polypropilene
Colour: black (code .09)
The 100 mm upper part must stay out of the ground level, according with the norms.

Miniloft spot



S.6665W 
 With 3 leds white **3000K** CRI90 426lm
 Rated luminaire luminous flux 324lm
 Rated input power 6W 230V



h(m)	9° Ø(m)	3000K E(lx)
1	0.16	7297
2	0.33	1824
3	0.49	811
4	0.66	456
5	0.82	292




S.6664W 
 With 3 leds white **3000K** CRI90 426lm
 Rated luminaire luminous flux 329lm
 Rated input power 6W 230V


h(m)	22° Ø(m)	3000K E(lx)
1	0.40	1860
2	0.79	465
3	1.19	207
4	1.58	116
5	1.98	74


Loft spot



S.6643W 
 With 5 leds white **3000K** CRI90 1285lm
 Rated luminaire luminous flux 1112lm
 Rated input power 17,7W 230V



h(m)	8° Ø(m)	3000K E(lx)
2	0.29	8556
4	0.59	2139
6	0.88	951
8	1.17	535
10	1.47	342




S.6649W 
 With 5 leds white **3000K** CRI90 1285lm
 Rated luminaire luminous flux 1032lm
 Rated input power 17,7W 230V


h(m)	29° Ø(m)	3000K E(lx)
2	1.04	996
4	2.08	249
6	3.13	111
8	4.17	62
10	5.21	40


Megaloft spot



S.6662W 
 With 9 leds white **3000K** CRI90 2310lm
 Rated luminaire luminous flux 1973lm
 Rated input power 30W 230V


h(m)	8° Ø(m)	3000K E(lx)
4	0.57	3762
8	1.15	941
12	1.72	418
16	2.29	235
20	2.87	150




S.6666W 
 With 9 leds white **3000K** CRI90 2310lm
 Rated luminaire luminous flux 1808lm
 Rated input power 30W 230V

h(m)	29° Ø(m)	3000K E(lx)
4	2.05	423
8	4.11	106
12	6.16	47
16	8.22	26
20	10.27	17

Megaloft flood asymmetric



S.6668 
 For lamp HIT-TC CRI 70W G8,5 6600lm
 Rated luminaire luminous flux 3432lm
 Rated input power 79W 230V

h(m)	E(lx)
10	6 6 3 2
8	12 10 6 3
6	35 24 11 3
4	90 58 11 3
2	47 19 3 1

3 m