MARKER / WALKER

MARKER

Marker is a product to be recessed in the steps and stair risers. It is distinguished by the complete absence of glare, given by an optical system engineered to maximize the orientation of the light downwards. Even where the lighting fixture is installed at a height higher than the point of view, visual comfort and safety are totally guaranteed.

TECHNICAL DESCRIPTION Die-cast aluminium housing with high corrosion resistance. Toughened glass diffuser. Stainless steel A4 screws. Luminaire with double cable entry and cable glands. Silicone gaskets. Double powder paint.

REGISTERED DESIGN

WALKER Neat lines, essential shapes, high performances: Walker is a wall recessed luminaire developed to enlight and ing glare a wide and well-directed light avoiding glare effects. The front frame, with no visible screws, is fixed through a spring locking system that preserves the elegant aesthetic.









www.simes.it/

PROTECTION CLASS

ISOLATION CLASS

MECHANICAL RESISTANCE IK 10 **3**03

COLOUR MARKER



.14 Aluminium Grey

COLOUR WALKER



.14 Aluminium Grey

MARKER

SIMES







S.6325W LED MODULE **3000K** CRI90 873Im 5,3W (on request 2700K CRI90 829Im) (on request 4000K CRI80 1072Im) 220V-240Vac 50/60Hz ON/OFF Not Dimmable

Recessing box not included Reinforced fixing system with screws



S.6329 RECESSING BOX for MARKER 305 x 79mm Depth 86mm

WALKER



	310	86	3
. 65]



S.6320W

LED MODULE **3000K** CRI90 1313Im 11,1W (on request 2700K CRI90 1247Im) (on request 4000K CRI80 1751Im) 220V-240Vac 50/60Hz **Phase-cut dimmer**

Version with DALI 2 power supply available on request with surcharge Recessing box not included Spring lock system for a total absence of visible screws



S.6329 RECESSING BOX for WALKER 305 x 79mm Depth 86mm

