




NH
HOTELES

Moai

Bollard

MOAI is a bollard with a strong personality and design. The smooth reflective surface guarantees an optimum light distribution. Its solid structure and robustness make it suitable for the installation in urban environment.





Ystad bathing pier, Sweden © Fagerhult Belysning AB

MOAI Bollard

Die-cast EN AB-47100 and extruded EN AW-6060 aluminium housing with high corrosion resistance.
Stainless steel screws.
99.98% pure aluminium reflectors.
Clear toughened reeded glass.
Pre-wired luminaire with neoprene cable and connector.
Silicone gaskets.
Double powder paint.

Protection class
IP65

Isolation class
CLASS I ⊕

Mechanical resistance
IK 06

Leds 4000K CR190 versions are available on request.



S.6159
ANTI GLARE SHIELD
for MINI MOAI





S.6169
ANTI GLARE SHIELD
for MOAI



S.5506
4 way connector for through wiring (in/out).


Colours:

-  Aluminium grey (code .14)
-  Burnished bronze (code 20)

For the latest technical information and luminaire updates with LED technology please refer to www.simes.it



REGISTERED DESIGN

H 800 mm



S.6150W

1 COB LED **3000K** CRI90 1565lm
 Rated luminaire luminous flux 584lm
 Rated input power 16,5W
 220V-240V AC 50/60Hz / DC Not Dimmable



Ø 120




S.6309

FLANGE ACCESSORY FOR MINIMOAI
 Ø 120 mm flange to be buried in concrete with stainless steel screws for fixing in the ground.



MOAI

H 1150 mm



S.6160W

1 COB LED **3000K** CRI90 3763lm
 Rated luminaire luminous flux 1375lm
 Rated input power 34,4W
 220V-240V AC 50/60Hz Not Dimmable



Ø 180



S.5310

FLANGE ACCESSORY FOR MOAI
 Ø 180 mm flange to be fixed in concrete with stainless steel screws for fixing in the ground.