




Plano

Walk over

PLANO is a elegant range of in-ground products that fulfill two important requirements: low surface temperature and flush with the floor. Such fitting is suitable for indoor as well as outdoor application and pedestrian areas, especially in those applications where we have people walking barefoot.





PLANO Walk over

Die cast EN AB-44100 aluminium housing (copper free) with high corrosion resistance.

Toughened glass diffuser
6mm thick for MINIPLANO,
8mm thick for PLANO,
8mm thick for MEGAPLANO.

Stainless steel screws.

Luminaire hard wired with single neoprene cable with cable gland.

Recessing box in polypropylene with external edge in stainless steel.

Silicone gaskets.

Double powdered paint.

Maximum weight 1000 Kg

For the latest technical information and product updates with LED technology please refer to the official website (www.simes.it)

Protection class

IP67

Isolation class

CLASS I ⊕

CLASS III ⚡ RGB


Mechanical resistance of glass

IK 09

Lamp HIT included.


Leds large beam versions are available on request.

Leds 4000K CR190 versions are available on request.



The recessing box must be placed at ground level.
20 cm drainage gravel must be used under the recessing box to allow easy water evacuation.
Connection to the main line has to be done into junction boxes.


Acid-etched glass




S.5434W

With led white **3000K** CRI90 140lm
 Rated luminaire luminous flux 35lm
 Rated input power 3W 230V
 Led position fixed

T 37°C






Semiacid-etched glass



S.5430W

With 3 leds white **3000K** CRI90 425lm
 Rated luminaire luminous flux 327lm
 Rated input power 6W 230V
 Adjustable $\pm 15^\circ$ optic


T 37°C



S.5438W


With 3 leds white **3000K** CRI90 425lm
 Rated luminaire luminous flux 329lm
 Rated input power 6W 230V
 Adjustable $\pm 15^\circ$ optic

T 37°C



PLANO Walk over \varnothing 190 mm


Acid-etched glass




S.5451W

With leds white **3000K** CRI90 420lm
 Rated luminaire luminous flux 45lm
 Rated input power 7,5W 230V
 Led position fixed

T 35°C






Semiacid-etched glass



S.5455W

With 5 leds white **3000K** CRI90 710lm
 Rated luminaire luminous flux 590lm
 Rated input power 9,1W 230V
 Adjustable $\pm 10^\circ$ optic


T 35°C



S.5444W



With 5 leds white **3000K** CRI90 710lm
 Rated luminaire luminous flux 578lm
 Rated input power 9,1W 230V
 Adjustable $\pm 10^\circ$ optic

T 35°C




MEGAPLANO Walk over \varnothing 260 mm

Acid-etched glass





S.5460W

With leds white **3000K** CRI90 945lm
 Rated luminaire luminous flux 137lm
 Rated input power 10,5W 230V
 Led position fixed
 T 35°C





Semiacid-etched glass




S.5425

With lamp HIT-TC CRI 20W G8,5 1700lm
 Rated luminaire luminous flux 1003lm
 Rated input power 22W 230V
 Lamp position fixed
 T 62°C





S.5427

With lamp HIT-TC CRI 35W G8,5 3300lm
 Rated luminaire luminous flux 1947lm
 Rated input power 37W 230V
 Lamp position fixed
 T 87°C





Semiacid-etched glass



S.5461W

With 9 leds white **3000K** CRI90 945lm
 Rated luminaire luminous flux 758lm
 Rated input power 10,5W 230V
 Adjustable $\pm 10^\circ$ optic
 T 35°C



S.5468W

With 9 leds white **3000K** CRI90 945lm
 Rated luminaire luminous flux 753lm
 Rated input power 10,5W 230V
 Adjustable $\pm 10^\circ$ optic
 T 35°C

