




Plano

Flush Walk-over

PLANO is a elegant range of in-ground luminaires that fulfill two important requirements: low surface temperature and flush with the floor. Such fitting is suitable for indoor as well as outdoor application and pedestrian areas, especially in those applications where we have people walking barefoot.





PLANO Flush Walk-over


Die cast EN AB-44100 aluminium housing with high corrosion resistance.
 Flush marine grade stainless steel AISI 316L front trim 2 mm thick with interlocking clips system and absence of visible screws (stainless-steel versions).
 Toughened glass diffuser
 6mm thick for Miniplano,
 8mm thick for Plano,
 8mm thick for Megaplano.
 Stainless steel screws.
 Pre-wired luminaire with neoprene cable and connector.
 Recessing box in polypropylene with external edge in stainless steel.
 Silicone gaskets.
Double powder paint.

Protection class
 IP65 / IP67

Isolation class
 CLASS I ⊕

Mechanical resistance
 IK 09

Leds 4000K CR190 versions are available on request.



The recessing box must be placed at ground level.
 20 cm drainage gravel must be used under the recessing box to allow easy water evacuation.
 Connection to the main line has to be done into junction boxes.




S.5506

4 way connector for through wiring (in/out).

Maximum weight 1000 Kg

For the latest technical information and luminaire updates with LED technology please refer to www.simes.it


Acid-etched glass




S.5434W

HIGH-POWER LED **3000K** CRI90 140lm
 Rated luminaire luminous flux 35lm
 Rated input power 3W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Led position fixed

T 37°C






Semiacid-etched glass



S.5430W

3 HIGH-POWER LEDs **3000K** CRI90 425lm
 Rated luminaire luminous flux 327lm
 Rated input power 6W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable $\pm 15^\circ$ optic


T 37°C



S.5438W

3 HIGH-POWER LEDs **3000K** CRI90 425lm
 Rated luminaire luminous flux 329lm
 Rated input power 6W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable $\pm 15^\circ$ optic

T 37°C




**Beam lenses available on request with no surcharge:
 34°**

T 37°C

MINIPLANO STAINLESS-STEEL Flush Walk-over


Acid-etched glass with no visible screw




S.5774W.19

HIGH-POWER LED **3000K** CRI90 140lm
 Rated luminaire luminous flux 35lm
 Rated input power 3W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Led position fixed

T 37°C






Semiacid-etched glass with no visible screw



S.5770W.19

3 HIGH-POWER LEDs **3000K** CRI90 425lm
 Rated luminaire luminous flux 327lm
 Rated input power 6W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable $\pm 15^\circ$ optic


T 37°C



S.5778W.19

3 HIGH-POWER LEDs **3000K** CRI90 425lm
 Rated luminaire luminous flux 329lm
 Rated input power 6W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable $\pm 15^\circ$ optic

T 37°C




**Beam lenses available on request with no surcharge:
 34°**

T 37°C

PLANO FULL-GLASS Flush Walk-over


Acid-etched glass




S.5451W □

HIGH-POWER LEDs **3000K** CRI90 1200lm
 Rated luminaire luminous flux 317lm
 Rated input power 10,1W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Led position fixed

T 35°C






Semiacid-etched glass




S.5455W □

5 HIGH-POWER LEDs **3000K** CRI90 710lm
 Rated luminaire luminous flux 590lm
 Rated input power 9,1W
 220V-240V AC 50/60Hz Not Dimmable
 Adjustable $\pm 10^\circ$ optic



S.5444W □

5 HIGH-POWER LEDs **3000K** CRI90 710lm
 Rated luminaire luminous flux 578lm
 Rated input power 9,1W
 220V-240V AC 50/60Hz Not Dimmable
 Adjustable $\pm 10^\circ$ optic




**Beam lenses available on request with no surcharge:
 38°, 58° and 10°x44°**

T 35°C

PLANO STAINLESS-STEEL Flush Walk-over


Acid-etched glass with no visible screw




S.5781W.19 □

HIGH-POWER LEDs **3000K** CRI90 1200lm
 Rated luminaire luminous flux 317lm
 Rated input power 10,1W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Led position fixed

T 35°C






Semiacid-etched glass with no visible screw




S.5785W.19 □

5 HIGH-POWER LEDs **3000K** CRI90 710lm
 Rated luminaire luminous flux 590lm
 Rated input power 9,1W
 220V-240V AC 50/60Hz Not Dimmable
 Adjustable $\pm 10^\circ$ optic



S.5784W.19 □

5 HIGH-POWER LEDs **3000K** CRI90 710lm
 Rated luminaire luminous flux 578lm
 Rated input power 9,1W
 220V-240V AC 50/60Hz Not Dimmable
 Adjustable $\pm 10^\circ$ optic




**Beam lenses available on request with no surcharge:
 38°, 58° and 10°x44°**


T 35°C

MEGAPLANO FULL-GLASS Flush Walk-over


Acid-etched glass





S.5460W □
 HIGH-POWER LEDs **3000K** CRI90 945lm
 Rated luminaire luminous flux 377lm
 Rated input power 11,10W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Led position fixed
 T 35°C





Semiacid-etched glass



S.5461W □
 9 HIGH-POWER LEDs **3000K** CRI90 945lm
 Rated luminaire luminous flux 758lm
 Rated input power 10,5W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable ±10° optic



S.5468W □
 9 HIGH-POWER LEDs **3000K** CRI90 945lm
 Rated luminaire luminous flux 753lm
 Rated input power 10,5W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable ±10° optic




**Beam lenses available on request with no surcharge:
 38°, 58° and 10°x44°**


T 35°C

MEGAPLANO STAINLESS-STEEL Flush Walk-over


Acid-etched glass with no visible screw





S.5790W.19 □
 HIGH-POWER LEDs **3000K** CRI90 945lm
 Rated luminaire luminous flux 377lm
 Rated input power 11,10W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Led position fixed
 T 35°C





Semiacid-etched glass with no visible screw



S.5791W.19 □
 9 HIGH-POWER LEDs **3000K** CRI90 945lm
 Rated luminaire luminous flux 758lm
 Rated input power 10,5W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable ±10° optic



S.5798W.19 □
 9 HIGH-POWER LEDs **3000K** CRI90 945lm
 Rated luminaire luminous flux 753lm
 Rated input power 10,5W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Adjustable ±10° optic



**Beam lenses available on request with no surcharge:
 38°, 58° and 10°x44°**

T 35°C