



Plano and Compact Comfort are two inground families characterized by a low recessed depth and great optical control. The lighting distribution on the surfaces is maximized and even more precise thanks to its tilttable optics.

TECHNICAL DESCRIPTION

Die cast aluminium housing with high corrosion resistance. Marine grade stainless steel AISI 316L front trim 2mm thick or aluminium. Stainless steel A4 screws. Luminaire supplied with neoprene H07RN-F cable and connector. Silicone gaskets. Double powder paint. Maximum weight 1000 Kg.

PLANO COMFORT

Toughened glass diffuser 6mm for PLANO COMFORT 120, 8mm PLANO COMFORT 190 and 260. Supplied with recessing box in polypropylene with external edge in stainless steel.

COMPACT COMFORT

Marine grade stainless steel AISI 316L front trim 2mm thick. Toughened glass diffuser 12mm. Supplied with recessing box in polypropylene.

PROTECTION CLASS
IP65 / IP67

ISOLATION CLASS
CLASS I Ⓢ

MECHANICAL RESISTANCE
IK 09

FINISHING COMPACT

.19 Stainless Steel




www.simes.it/plano-compact





"Masseria Ciura", Massara, Italy © Arch. Giampaolo Bianco

Ø 120mm - Acid-etched glass




S.5434W Diffused beam
 LED MODULE **3000K** CRI90 194lm 1,5W
 (on request 2700K CRI90 179lm)
 (on request 4000K CRI80 238lm)
 220V-240Vac 50/60Hz
 ON/OFF Not Dimmable
 Fixed LED position

Ø 120mm - Transparent glass




S.5426W Spot beam with lenses
 LED MODULE **3000K** CRI90 520lm 4,3W
 (on request 2700K CRI90 480lm)
 (on request 4000K CRI80 640lm)
 220V-240Vac 50/60Hz
 ON/OFF Not Dimmable
 Adjustable ±15° optic



S.5428W Medium beam with lenses
 LED MODULE **3000K** CRI90 520lm 4,3W
 (on request 2700K CRI90 480lm)
 (on request 4000K CRI80 640lm)
 220V-240Vac 50/60Hz
 ON/OFF Not Dimmable
 Adjustable ±15° optic


Beam lenses available on request with no surcharge:
 65°, 10°x44° and asymmetric

Ø 190mm - Acid-etched glass




S.5451W Diffused beam
LED MODULE **3000K** CRI90 1106lm 8,7W
(on request 2700K CRI90 1087lm)
(on request 4000K CRI80 1490lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable
Fixed LED position

Ø 190mm - Transparent glass




S.5440W Spot beam with lenses
LED MODULE **3000K** CRI90 1265lm 9,8W
(on request 2700K CRI90 1167m)
(on request 4000K CRI80 1557lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable
Adjustable ±10° optic




S.5441W Medium beam with lenses
LED MODULE **3000K** CRI90 1265lm 9,8W
(on request 2700K CRI90 1167m)
(on request 4000K CRI80 1557lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable
Adjustable ±10° optic

Beam lenses available on request with no surcharge:
65°, 10°x44° and asymmetric




Ø 200mm - Acid etched glass




S.5181W.19 Diffused beam
LED MODULE **3000K** CRI90 1106lm 8,7W
(on request 2700K CRI90 1087lm, 4000K CRI80 1490lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable
Fixed LED position

Ø 200mm - Transparent glass




S.5110W.19 Spot beam with lenses
LED MODULE **3000K** CRI90 1265lm 9,8W
(on request 2700K CRI90 1167m)
(on request 4000K CRI80 1557lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable
Adjustable ±10° optic




S.5111W.19 Medium beam with lenses
LED MODULE **3000K** CRI90 1265lm 9,8W
(on request 2700K CRI90 1167m)
(on request 4000K CRI80 1557lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable
Adjustable ±10° optic

Beam lenses available on request with no surcharge:
65°, 10°x44° and asymmetric




Ø 260mm - Acid-etched glass




S.5460W Diffused beam
LED MODULE **3000K** CRI90 1215lm 9,0W
(on request 2700K CRI90 1125lm)
(on request 4000K CRI80 1305lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable
Fixed LED position

Ø 260mm - Transparent glass




S.5465W Spot beam with lenses
LED MODULE **3000K** CRI90 2249lm 17,4W
(on request 2700K CRI90 2075lm)
(on request 4000K CRI80 2768lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable
Adjustable ±10° optic




S.5466W Medium beam with lenses
LED MODULE **3000K** CRI90 2249lm 17,4W
(on request 2700K CRI90 2075lm)
(on request 4000K CRI80 2768lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable
Adjustable ±10° optic

Beam lenses available on request with no surcharge:
65°, 10°x44° and asymmetric




Ø 275mm - Acid etched glass




S.5128W.19 Diffused beam
LED MODULE **3000K** CRI90 1215lm 9,0W
(on request 2700K CRI90 1125lm)
(on request 4000K CRI80 1305lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable
Fixed LED position

Ø 275mm - Transparent glass



S.5135W.19 Spot beam with lenses
LED MODULE **3000K** CRI90 2249lm 17,4W
(on request 2700K CRI90 2075lm)
(on request 4000K CRI80 2768lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable
Adjustable ±10° optic



S.5136W.19 Medium beam with lenses
LED MODULE **3000K** CRI90 2249lm 17,4W
(on request 2700K CRI90 2075lm)
(on request 4000K CRI80 2768lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable
Adjustable ±10° optic

Beam lenses available on request with no surcharge:
65°, 10°x44° and asymmetric

