

PLAN Wall mounted

SIMES

PLAN

Characterized by simple but rigorous design and a soft and diffused beam, Plan is LED wall mounted luminaire in single or double emission. Its protruding frosted glass creates a pleasant and elegant luminous sign.

TECHNICAL DESCRIPTION

Die-cast aluminium housing with high corrosion resistance. Toughened acid-etched decorative glass diffuser. Stainless steel A4 screws. Silicone gaskets. Double powder paint.

MINIPLAN HORIZONTAL

Luminaire supplied with 1,0m neoprene H05RN-F cable.

PLAN HORIZONTAL

Luminaire with one single cable entry and grommet.

REGISTERED DESIGN

PROTECTION CLASS
IP65

ISOLATION CLASS

CLASS I ⊕ PLAN HORIZONTAL
CLASS II ⊞ MINIPLAN HORIZONTAL

MECHANICAL RESISTANCE

IK 06



COLOURS


.01 White

.14 Aluminium Grey





www.simes.it/plan


MINIPLAN Horizontal




S.3883W Single emission
LED MODULE **3000K** CRI90 1313lm 11,1W
(on request 2700K CRI90 1247lm
(on request 4000K CRI80 1751lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable



S.3884W Double emission
LED MODULE **3000K** CRI90 1313lm 11,1W
(on request 2700K CRI90 1247lm
(on request 4000K CRI80 1751lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable





PLAN Horizontal



S.3893W Single emission
LED MODULE **3000K** CRI90 2100lm 17,8W
(on request 2700K CRI90 1995lm
(on request 4000K CRI80 2801lm)
220V-240Vac 50/60Hz
Phase-cut dimmer

Version with DALI 2 / PUSH power supply
available on request with surcharge.



S.3894W Double emission
LED MODULE **3000K** CRI90 2100lm 17,8W
(on request 2700K CRI90 1995lm
(on request 4000K CRI80 2801lm)
220V-240Vac 50/60Hz
Phase-cut dimmer

Version with DALI 2 / PUSH power supply
available on request with surcharge.



SIMES

