

Pocket is a slim wall applique in single and double emission that designs striking lighting effects on the wall surface. The fixture is installed through a clip-on system and a special base anchored to the wall, leading to a user friendly installation. The complete range is characterized by clean and rounded shapes with no visible screws, enhancing its elegant but sober design. Pocket is available in two square and two rectangular versions.

TECHNICAL DESCRIPTION

Die-cast aluminium housing with high corrosion resistance. Toughened glass diffuser. Stainless steel A4 screws. Luminaire supplied with 5,0m neoprene H05RN-F cable. Electronic power supply included. Silicone gaskets. Double powder paint.

REGISTERED DESIGN

PROTECTION CLASS
IP65

ISOLATION CLASS
CLASS II □ POCKET LONG
CLASS I ⊕

MECHANICAL RESISTANCE
IK 06

COLOURS

.01 White

.14 Aluminium Grey

.24 Anthracite Grey




POCKET Square


SIMES

POCKET Rectangular



SIMES



S.1850W Single emission
LED MODULE **3000K** CRI90 625lm 4,5W
(on request 2700K CRI90 575lm)
(on request 4000K CRI80 725lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable




S.1851W Double emission
2 x LED MODULE **3000K** CRI90 625lm 4,5W
(on request 2700K CRI90 575lm)
(on request 4000K CRI80 725lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable




S.1870W Single emission
LED MODULE **3000K** CRI90 1760lm 12,5W
(on request 2700K CRI90 1619lm)
(on request 4000K CRI80 2042lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable

Version with DALI 2 / PUSH power supply available on request with surcharge.




S.1871W Double emission
2 x LED MODULE **3000K** CRI90 1760lm 12,5W
(on request 2700K CRI90 1619lm)
(on request 4000K CRI80 2042lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable

Version with DALI 2 / PUSH power supply available on request with surcharge.




POCKET Square



POCKET Long




S.1860W Single emission
LED MODULE **3000K** CRI90 1250lm 8,8W
(on request 2700K CRI90 1150lm)
(on request 4000K CRI80 1450lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable



S.1861W Double emission
2 x LED MODULE **3000K** CRI90 1250lm 8,8W
(on request 2700K CRI90 1150lm)
(on request 4000K CRI80 1450lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable



S.1880W Single emission
LED MODULE **3000K** CRI90 2916lm 20,6W
(on request 2700K CRI90 2683lm)
(on request 4000K CRI80 3383lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable



S.1881W Double emission
2 x LED MODULE **3000K** CRI90 2916lm 20,6W
(on request 2700K CRI90 2683lm)
(on request 4000K CRI80 3383lm)
220V-240Vac 50/60Hz
ON/OFF Not Dimmable

