

Pool is a high performance underwater luminaire designed specifically for swimming pools and fountains. Available in three dimensions, it is equipped with LED light sources, monochromatic and RGBW, for emotional and charming effects.

TECHNICAL DESCRIPTION

Technopolymer housing. Marine grade stainless steel AISI 316L front trim 2mm thick. Toughened glass diffuser 10mm thick for MICROPOOL, 12mm thick for MINIPOOL, 12mm thick for POOL, 4mm thick for MICROPOOL SPOT, 8mm thick for MINIPOOL SPOT, 8mm thick for POOL SPOT. Luminaire supplied with 6,0m neoprene HO7RN-F cable for submersion cable with cable gland. Stainless steel A4 screws. Corrugated plastic pipe 5,0m long for MICROPOOL and MINIPOOL, 7,0m long for POOL. Silicone gaskets.

PROTECTION CLASS
IP68 3m

ISOLATION CLASS
CLASS III

MECHANICAL RESISTANCE
IK 10

Power supply not included.

Suitable for swimming pools in concrete and metal, recessed to the wall and on the bottom.

Not suitable for submersion in salt water.

POOL RECESSED

Recessing box in technopolymer with front ring in stainless steel AISI 316L.

REGISTERED DESIGN


FINISHING

.19 STAINLESS STEEL



www.simes.it/pool


Micropool



S.3607.19 Medium beam with lens
LED MODULE **6000K** CRI70 285lm 2,5W
24Vdc PWM


Requires constant voltage 24Vdc remote power supply (page 522-523) *

RGBW




S.3603.19 Medium beam with lenses
LED MODULE **RGBW (W=6000K)** 70lm 0,5W
24Vdc PWM

Requires constant voltage remote power supply for RGBW and DMX or DALI controllers (page 528-529)




Minipool



S.3617.19 Flood beam with lenses
LED MODULE **6000K** CRI70 1670lm 20W
24Vdc NOT DIMMABLE


Requires constant voltage 24Vdc remote power supply (page 522) *

RGBW




S.3629.19 Flood beam with lenses
LED MODULE **RGBW (W=6000K)** 1083lm 7,8W
24Vdc PWM

Requires constant voltage remote power supply for RGBW and DMX or DALI controllers (page 528-529)




Pool



S.3627.19 Flood beam with lenses
LED MODULE **6000K** CRI70 3340lm 34W
24Vdc NOT DIMMABLE


Requires constant voltage 24Vdc remote power supply (page 522) *

RGBW




S.3630.19 Flood beam with lenses
LED MODULE **RGBW (W=6000K)** 2951lm 21,4W
24Vdc PWM

Requires constant voltage remote power supply for RGBW and DMX or DALI controllers (page 528-529)



* Micropool, Minipool and Pool with 6000K LED work also with traditional systems 12Vac (proper to substitute existing lamps for swimming pool with magnetic transformer 230V/12Vac).


Micropool



S.3676.19 Medium beam with lens
LED MODULE 6000K CRI70 285lm 2,5W
24Vdc PWM


Requires constant voltage 24Vdc remote power supply (page 522-523) *

RGBW



S.3673.19 Medium beam with lenses
LED MODULE RGBW (W=6000K) 70lm 0,5W
24Vdc PWM

Requires constant voltage remote power supply for RGBW and DMX or DALI controllers (page 528-529)




S.3671



FLANGE for MICROPOL and MINIPOL SPOT
Fixation base plate for Micro and Minipool Spot installation.
Weight of the flange: Kg 1,5


Minipool



S.3686.19 Flood beam with lenses
LED MODULE 6000K CRI70 1670lm 20W
24Vdc NOT DIMMABLE


Requires constant voltage 24Vdc remote power supply (page 522) *

RGBW



S.3683.19 Flood beam with lenses
LED MODULE RGBW (W=6000K) 1083lm 7,8W
24Vdc PWM

Requires constant voltage remote power supply for RGBW and DMX or DALI controllers (page 528-529)





S.3671



FLANGE for MICROPOL and MINIPOL SPOT
Fixation base plate for Micro and Minipool Spot installation.
Weight of the flange: Kg 1,5



Pool



S.3696.19 Flood beam with lenses
LED MODULE 6000K CRI70 3340lm 34W
24Vdc NOT DIMMABLE


Requires constant voltage 24Vdc remote power supply (page 522) *

RGBW



S.3693.19 Flood beam with lenses
LED MODULE RGBW (W=6000K) 2951lm 21,4W
24Vdc PWM

Requires constant voltage remote power supply for RGBW and DMX or DALI controllers (page 528-529)



S.3672



FLANGE for POOL SPOT
Fixation base plate for Pool Spot installation.
Weight of the flange: Kg 3,5

* Micropool, Minipool and Pool with 6000K LED work also with traditional systems 12Vac (proper to substitute existing lamps for swimming pool with magnetic transformer 230V/12Vac).

