Ghost per cemento Design M. Sadler

Ghost for cast concrete


SEGNAPASSO DA INCASSO Step light wall recessed




L.75 H.350



L.290 H.100



L.210 H.260



L.155 H.190



L.90 H.100



L.1570 H.48



L.810 H.48



L.430 H.48



L.240 H.48



MENZIONE D'ONORE
COMPASSO D ORO ADI

SIMES

"Collina degli studenti", Campus Bovisa - La Masa, Politecnico di Milano, Italy © Ph. Mario Bertani



Seaplan Lagoon, Alameda, California - Arch. Mary Wong Donn Logan © Ph. Billy Hustace Photography

Ghost per cemento Design M. Sadler

Ghost for cast concrete

DESCRIZIONE TECNICA Technical description
Struttura in alluminio pressofuso. Cassaforma in polipropilene per Ghost. Diffusore in vetro temprato acidato extrachiaro per Ghost. Cassaforma in alluminio estruso per Ghost lineare. Diffusore in resina trasparente per Ghost lineare. Precablato con cavo. Die-cast aluminum housing. Polypropylene recessing box for Ghost. Extra-clear acid-etched toughened glass diffuser for Ghost. Extruded aluminum recessing box for Ghost linear. Transparent resin diffuser for linear Ghost. Pre-wired luminaire.

INFORMAZIONI GENERALI General information	
GRADO DI PROTEZIONE IP rating	**IP65**
CLASSE DI ISOLAMENTO Insulation class	**CLASS I ⏚ (Ghost verticale)**
	CLASS III ◈ (24Vdc)
RESISTENZA IMPATTO Mechanical resistance	**IK 10**


FINITURE Finishing
Cemento utilizzato per il getto. Materiale soggetto ad invecchiamento naturale. Concrete used for the casting process. Natural ageing material.
BREVETTATO Patented
MODELLO REGISTRATO Registered design

SEGNAPASSO DA INCASSO

Step light wall recessed

GHOST ORIZZONTALE L290


Ghost horizontal L290



CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
C.8020H	2700 K		80	534 lm	7.2 W	24 Vdc remote (p.554)	PWM
C.8020W	3000 K		80	634 lm	7.2 W	24 Vdc remote (p.554)	PWM
C.8020N	4000 K		80	634 lm	7.2 W	24 Vdc remote (p.554)	PWM

GHOST VERTICALE H350


Ghost vertical H350



CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
C.8024H	2700 K		80	653 lm	7.5 W	220-240 Vac	Dali2/Push
C.8024W	3000 K		80	689 lm	7.5 W	220-240 Vac	Dali2/Push
C.8024N	4000 K		80	697 lm	7.5 W	220-240 Vac	Dali2/Push

MICROGHOST QUADRATO H100


Microghost square H100



CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
C.8030H	2700 K		80	189 lm	2.8 W	24 Vdc remote (p.554)	PWM
C.8030W	3000 K		80	224 lm	2.8 W	24 Vdc remote (p.554)	PWM
C.8030N	4000 K		80	224 lm	2.8 W	24 Vdc remote (p.554)	PWM

MINIGHOST QUADRATO H190


Minighost square H190



CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
C.8027H	2700 K		80	277 lm	3.4 W	24 Vdc remote (p.554)	PWM
C.8027W	3000 K		80	329 lm	3.4 W	24 Vdc remote (p.554)	PWM
C.8027N	4000 K		80	329 lm	3.4 W	24 Vdc remote (p.554)	PWM

GHOST QUADRATO H260


Ghost square H260



CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
C.8025H	2700 K		80	718 lm	9.7 W	24 Vdc remote (p.554)	PWM
C.8025W	3000 K		80	853 lm	9.7 W	24 Vdc remote (p.554)	PWM
C.8025N	4000 K		80	853 lm	9.7 W	24 Vdc remote (p.554)	PWM

GHOST LINEARE L240

Ghost Linear L240




CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
C.8034H	2700 K		80	332 lm	3.8 W	220-240 Vac	ON-OFF
C.8034W	3000 K		80	394 lm	3.8 W	220-240 Vac	ON-OFF
C.8034N	4000 K		80	394 lm	3.8 W	220-240 Vac	ON-OFF

ACCESSORI PER GHOST LINEARE L240 Accessories for Ghost Linear L240

C.8033 *Accessorio dima per per foratura del cassero per Ghost Lineare L240
*Drilling jig for shutter for Ghost Linear L240

GHOST LINEARE L430

Ghost Linear L430




CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
C.8036H	2700 K		80	663 lm	7.5 W	220-240 Vac	ON-OFF
C.8036W	3000 K		80	788 lm	7.5 W	220-240 Vac	ON-OFF
C.8036N	4000 K		80	788 lm	7.5 W	220-240 Vac	ON-OFF

ACCESSORI PER GHOST LINEARE L430 Accessories for Ghost Linear L430

C.8035 *Accessorio dima per per foratura del cassero per Ghost Lineare L430
*Drilling jig for shutter for Ghost Linear L430

GHOST LINEARE L810

Ghost Linear L810




CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
C.8038H	2700 K		80	1326 lm	14.0 W	220-240 Vac	ON-OFF
C.8038W	3000 K		80	1576 lm	14.0 W	220-240 Vac	ON-OFF
C.8038N	4000 K		80	1576 lm	14.0 W	220-240 Vac	ON-OFF

ACCESSORI PER GHOST LINEARE L810 Accessories for Ghost Linear L810

C.8037 *Accessorio dima per foratura del cassero per Ghost Lineare L810
*Drilling jig for shutter for Ghost Linear L810

GHOST LINEARE L1570

Ghost Linear L1570



CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
C.8040H	2700 K		80	2653 lm	28.0 W	220-240 Vac	ON-OFF
C.8040W	3000 K		80	3152 lm	28.0 W	220-240 Vac	ON-OFF
C.8040N	4000 K		80	3152 lm	28.0 W	220-240 Vac	ON-OFF

ACCESSORI PER GHOST LINEARE L1570 Accessories for Ghost Linear L1570

C.8039 *Accessorio dima per foratura del cassero per Ghost Lineare L1570
*Drilling jig for shutter for Ghost Linear L1570

***** La dima per foratura del cassero facilita l'esecuzione di Ghost in linea continua.
E' necessaria una sola dima per ogni dimensione impiegata perchè la dima può essere riutilizzata.

* The drilling jig facilitates the execution of Ghost in a continuous line.
Only one jig is needed for each size used because the jig can be reused.