

SOFFITTO DA SUPERFICIE Ceiling surface mounted



Ø 200 H.320



Ø 140 H.290



Ø 90 H.165

PARETE Wall mounted



Ø 200 H.450



Ø 140 H.350



Ø 90 H.250





Slot

DESCRIZIONE TECNICA Technical description	INFORMAZIONI GENERALI General information		CODICI COLORE Colour codes
Struttura in alluminio pressofuso ed estruso. Viti in acciaio con rivestimento anticorrosivo. Vetro trasparente temprato di protezione. Slot e Minislot precablati con cavo. Predisposto per cablaggio passante con passafilo per Microslot. Die-cast and extruded aluminum housing. Steel screws with anticorrosive coating. Transparent protective toughened glass. Pre-wired Slot and Minislot. Prepared for through-wiring with cable gland for Microslot.	GRADO DI PROTEZIONE IP rating	IP65	.14 Grigio alluminio Aluminium Grey .24 Grigio antracite Anthracite Grey
	CLASSE DI ISOLAMENTO Insulation class	CLASS I ⚡	
	RESISTENZA IMPATTO Mechanical resistance	IK 08	

PARETE
Wall mounted

MICROSLOT Ø90

	CODE	CCT	OPTIC	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	S.3814H	2700 K	Fascio largo singola emissione		90	536 lm	7.1 W	220-240 Vac	ON-OFF
	S.3814W	3000 K	Wide beam		90	583 lm	7.1 W	220-240 Vac	ON-OFF
	S.3814N	4000 K	single emission		90	638 lm	7.1 W	220-240 Vac	ON-OFF
	S.3815H	2700 K	Fascio largo doppia emissione		90	1072 lm	13.2 W	220-240 Vac	ON-OFF
	S.3815W	3000 K	Wide beam		90	1166 lm	13.2 W	220-240 Vac	ON-OFF
	S.3815N	4000 K	double emission		90	1276 lm	13.2 W	220-240 Vac	ON-OFF

MINISLOT Ø140

	CODE	CCT	OPTIC	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	S.3824H	2700 K	Fascio medio singola emissione		90	1224 lm	16.6 W	220-240 Vac	Dali2/Push
	S.3824W	3000 K	Medium beam		90	1317 lm	16.6 W	220-240 Vac	Dali2/Push
	S.3824N	4000 K	single emission		90	1435 lm	16.6 W	220-240 Vac	Dali2/Push
	S.3825H	2700 K	Fascio medio doppia emissione		90	2448 lm	30.4 W	220-240 Vac	Dali2/Push
	S.3825W	3000 K	Medium beam		90	2634 lm	30.4 W	220-240 Vac	Dali2/Push
	S.3825N	4000 K	double emission		90	2870 lm	30.4 W	220-240 Vac	Dali2/Push

SLOT Ø200

	CODE	CCT	OPTIC	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	S.3834H	2700 K	Fascio medio singola emissione		90	2560 lm	27.4 W	220-240 Vac	Dali2/Push
	S.3834W	3000 K	Medium beam		90	2715 lm	27.4 W	220-240 Vac	Dali2/Push
	S.3834N	4000 K	single emission		90	2947 lm	27.4 W	220-240 Vac	Dali2/Push
	S.3835H	2700 K	Fascio medio doppia emissione		90	5120 lm	53.6 W	220-240 Vac	Dali2/Push
	S.3835W	3000 K	Medium beam		90	5430 lm	53.6 W	220-240 Vac	Dali2/Push
	S.3835N	4000 K	double emission		90	5894 lm	53.6 W	220-240 Vac	Dali2/Push

SOFFITTO DA SUPERFICIE
Ceiling surface mounted

SIMES

MICROSLOT DOWNLIGHT Ø90

	CODE	CCT	OPTIC	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	S.3817H	2700 K	Fascio largo con riflettore Wide beam with reflector		90	536 lm	7.1 W	220-240 Vac	ON-OFF
	S.3817W	3000 K			90	583 lm	7.1 W	220-240 Vac	ON-OFF
	S.3817N	4000 K			90	638 lm	7.1 W	220-240 Vac	ON-OFF

MINISLOT DOWNLIGHT Ø140

	CODE	CCT	OPTIC	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	S.3827H	2700 K	Fascio extra largo con riflettore Extra wide beam with reflector		90	1420 lm	16.6 W	220-240 Vac	Dali2/Push
	S.3827W	3000 K			90	1528 lm	16.6 W	220-240 Vac	Dali2/Push
	S.3827N	4000 K			90	1665 lm	16.6 W	220-240 Vac	Dali2/Push

SLOT DOWNLIGHT Ø200

	CODE	CCT	OPTIC	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	S.3837H	2700 K	Fascio extra largo con riflettore Extra wide beam with reflector		90	2560 lm	27.4 W	220-240 Vac	Dali2/Push
	S.3837W	3000 K			90	2718 lm	27.4 W	220-240 Vac	Dali2/Push
	S.3837N	4000 K			90	2950 lm	27.4 W	220-240 Vac	Dali2/Push