Stick

PALETTO Bollard



Ø 76 H.800 | Ø 76 H.360 | Ø 38 H.220

Stick


DESCRIZIONE TECNICA Technical description
Struttura in alluminio pressofuso. Paletto in alluminio estruso. Stick con vetro trasparente temprato. Ministick con diffusore in resina opale. Viti in acciaio con rivestimento anticorrosivo. Precablato con cavo. Die-cast aluminium structure. Extruded aluminum bollard. Stick with transparent toughened glass. Ministick with opal resin diffuser. Steel screws with anticorrosive coating. Pre-wired luminaire.

INFORMAZIONI GENERALI General information	
GRADO DI PROTEZIONE IP rating	**IP54**
CLASSE DI ISOLAMENTO Insulation class	**CLASS I ⏚ (Stick)**
	CLASS III ◈ (Ministick)
RESISTENZA IMPATTO Mechanical resistance	**IK 06**

CODICI COLORE Colour codes
.09 Nero Black
.24 Grigio antracite Anthracite Grey
MODELLO REGISTRATO Registered design


PALETTO Ø38
Bollard Ø38

MINISTICK Ø38 H220 180°




CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
S.2080H	2700 K		80	81 lm	3.1 W	24 Vdc remote (p.554)	PWM
S.2080W	3000 K		80	83 lm	3.1 W	24 Vdc remote (p.554)	PWM
S.2080N	4000 K		80	85 lm	3.1 W	24 Vdc remote (p.554)	PWM

MINISTICK Ø38 H220 360°



CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
S.2081H	2700 K		80	172 lm	5.2 W	24 Vdc remote (p.554)	PWM
S.2081W	3000 K		80	177 lm	5.2 W	24 Vdc remote (p.554)	PWM
S.2081N	4000 K		80	182 lm	5.2 W	24 Vdc remote (p.554)	PWM




ACCESSORI PER TUTTE LE VERSIONI DI MINISTICK Accessories for all Ministick versions

S.2088 Picchetto per Ministick Spike for Ministick


PALETTO Ø76
Bollard Ø76

STICK Ø76 H360 180°




CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
S.2090H	2700 K		80	165 lm	7.5 W	220-240Vac	Dali2/Push
S.2090W	3000 K		80	178 lm	7.5 W	220-240Vac	Dali2/Push
S.2090N	4000 K		80	191 lm	7.5 W	220-240Vac	Dali2/Push

STICK Ø76 H360 360°




CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
S.2091H	2700 K		80	326 lm	13.6 W	220-240Vac	Dali2/Push
S.2091W	3000 K		80	352 lm	13.6 W	220-240Vac	Dali2/Push
S.2091N	4000 K		80	378 lm	13.6 W	220-240Vac	Dali2/Push



ACCESSORI PER TUTTE LE VERSIONI DI STICK H360 Accessories for all Stick H360 versions

S.2098 Picchetto per Stick H360 Spike for Stick H360




S.2099 Flangia da interrare per Stick Flange to be buried for Stick

STICK Ø76 H800 180°




CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
S.2095H	2700 K		80	165 lm	7.5 W	220-240 Vac	Dali2/Push
S.2095W	3000 K		80	178 lm	7.5 W	220-240 Vac	Dali2/Push
S.2095N	4000 K		80	191 lm	7.5 W	220-240 Vac	Dali2/Push

STICK Ø76 H800 360°



CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
S.2096H	2700 K		80	326 lm	13.6 W	220-240 Vac	Dali2/Push
S.2096W	3000 K		80	352 lm	13.6 W	220-240 Vac	Dali2/Push
S.2096N	4000 K		80	378 lm	13.6 W	220-240 Vac	Dali2/Push



ACCESSORI PER TUTTE LE VERSIONI DI STICK Accessories for all Stick versions

S.2099 Flangia da interrare per Stick Flange to be buried for Stick