






# Slot

## Wall effect

High flexibility can be considered one of the main plus of SLOT. Able to ensure functional lighting with excellent light output, SLOT also allow to create more or less marked light accents suitable for variuos applications. The double emission versions house two LED sources, each one with its own adjustable reflector and independent control gear.





## SLOT Wall effect

Die-cast EN AB-47100 and extruded EN AW-6060 aluminium housing with high corrosion resistance.  
Toughened glass diffuser  
6mm thick for Microslot,  
8mm thick for Minislot,  
8mm thick for Slot.  
Luminaire with one single cable entry and grommet (Microslot).  
Pre-wired luminaire with single cable and connector.  
Stainless steel screws.  
Silicone gaskets.  
**Double powder paint.**

### Colour:

○ Aluminium grey (code 14)

### Protection class

IP65

### Isolation class

CLASS I ⊕





### Mechanical resistance

IK 08

Leds 4000K CRI90 versions are available on request.

*For the latest technical information and luminaire updates with LED technology please refer to [www.simes.it](http://www.simes.it)*

## Wall single emission





### S.3903W

HIGH-POWER LEDs **3000K** CRI90 425lm  
 Rated luminaire luminous flux 327lm  
 Rated input power 6W  
 220V-240V AC 50/60Hz / DC Not Dimmable  
 Adjustable  $\pm 15^\circ$  optic

h(m)	9° Ø(m)	3000K E(lx)
1	0.16	7297
2	0.33	1824
3	0.49	811
4	0.66	456
5	0.82	292

**Beam lenses available on request with no surcharge:  
 22° and 34°**

## Wall double emission



### S.3913W



HIGH-POWER LEDs **3000K** CRI90 425lm  
 Rated luminaire luminous flux 654lm  
 Rated input power 12W  
 220V-240V AC 50/60Hz / DC Not Dimmable  
 Adjustable  $\pm 15^\circ$  optic

h(m)	9° Ø(m)	3000K E(lx)
1	0.16	7297
2	0.33	1824
3	0.49	811
4	0.66	456
5	0.82	292

**Beam lenses available on request with no surcharge:  
 22° and 34°**

# MINISLOT ROUND

## Wall single emission





### S.3950W

HIGH-POWER LEDs **3000K** CRI90 1180lm  
 Rated luminaire luminous flux 834lm  
 Rated input power 16W  
 220V-240V AC 50/60Hz / DC Not Dimmable  
 Adjustable  $\pm 15^\circ$  optic

h(m)	28° Ø(m)	3000K E(lx)
2	1.00	833
4	2.01	208
6	3.01	93
8	4.02	52
10	5.02	33

**Beam lenses available on request with no surcharge:  
 8°, 38°, 58° and 10°x44°**

## Wall double emission




### S.3952W

HIGH-POWER LEDs **3000K** CRI90 2360lm  
 Rated luminaire luminous flux 1668lm  
 Rated input power 32W  
 220V-240V AC 50/60Hz / DC Not Dimmable  
 Adjustable  $\pm 15^\circ$  optic

h(m)	28° Ø(m)	3000K E(lx)
2	1.00	833
4	2.01	208
6	3.01	93
8	4.02	52
10	5.02	33

**Beam lenses available on request with no surcharge:  
 8°, 38°, 58° and 10°x44°**

## Wall single emission




### S.3960W

HIGH-POWER LEDs **3000K** CR190 2125lm  
 Rated luminaire luminous flux 1332lm  
 Rated input power 27W  
 220V-240V AC 50/60Hz / DC Not Dimmable  
 Adjustable  $\pm 15^\circ$  optic

h(m)	29° Ø(m)	3000K E(lx)
2	1.06	1243
4	2.11	311
6	3.17	138
8	4.23	78
10	5.28	50

**Beam lenses available on request with no surcharge:  
 8°, 38°, 58° and 10°x44°**

## Wall double emission



### S.3962W

HIGH-POWER LEDs **3000K** CR190 4248lm  
 Rated luminaire luminous flux 2664lm  
 Rated input power 54W  
 220V-240V AC 50/60Hz / DC Not Dimmable  
 Adjustable  $\pm 15^\circ$  optic

h(m)	29° Ø(m)	3000K E(lx)
2	1.06	1243
4	2.11	311
6	3.17	138
8	4.23	78
10	5.28	50

**Beam lenses available on request with no surcharge:  
 8°, 38°, 58° and 10°x44°**



Mansfield Bus Station, Nottinghamshire, England