

## SLOT Ceiling and wall mounted

SIMES



## SLOT

Slot is an iconic family of Simes composed of cylinders for ceiling or wall, offered in three different sizes, with a great mechanical resistance and tiltable optics designed on the COB source. The aluminium double inner reflectors assure high comfort lighting with reduced glare, maintaining high performances. The wall version is available both with single or double emission. This last one with two independent adjustable reflectors and lighting management.

### TECHNICAL DESCRIPTION

Die-cast and extruded aluminium housing with high corrosion resistance. Stainless steel A4 screws. Silicone gaskets. Double powder paint.

### MICROSLOT

Luminaire with one single cable entry and grommet. Toughened glass diffuser 6mm.

### MINISLOT

Luminaire supplied with neoprene H05RN-F cable and connector. Toughened glass diffuser 8mm.

### SLOT

Luminaire supplied with neoprene H05RN-F cable and connector. Toughened glass diffuser 8mm.

PROTECTION CLASS  
IP65

ISOLATION CLASS  
CLASS I

MECHANICAL RESISTANCE  
IK 06

### COLOURS



.14 Aluminium Grey

.24 Anthracite Grey




[www.simes.it/slot](http://www.simes.it/slot)

Microslot





**S.3814W Single Flood beam with reflector**  
 LED MODULE **3000K** CRI90 657lm 6,6W  
 (on request 2700K CRI90 627lm)  
 (on request 4000K CRI80 837lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable  
 Adjustable  $\pm 15^\circ$  optic




**S.3815W Double Flood beam with reflector**  
 2 x LED MODULE **3000K** CRI90 657lm 6,6W  
 (on request 2700K CRI90 627lm)  
 (on request 4000K CRI80 837lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable  
 Adjustable  $\pm 15^\circ$  optic

Minislot





**S.3824W Single Medium beam with reflector**  
 LED MODULE **3000K** CRI90 2034lm 15,5W  
 (on request 2700K CRI90 1933lm)  
 (on request 4000K CRI80 2493lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable  
 Adjustable  $\pm 15^\circ$  optic




**S.3825W Double Medium beam with reflector**  
 2 x LED MODULE **3000K** CRI90 2034lm 15,5W  
 (on request 2700K CRI90 1933lm)  
 (on request 4000K CRI80 2493lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable  
 Adjustable  $\pm 15^\circ$  optic

Slot





**S.3834W Single Flood beam with reflector**  
 LED MODULE **3000K** CRI90 3636lm 28W  
 (on request 2700K CRI90 3456lm)  
 (on request 4000K CRI80 4456lm)  
 220V-240Vac 50/60Hz  
**Dimmable DALI 2 / PUSH**  
 Adjustable  $\pm 15^\circ$  optic





**S.3835W Double Flood beam with reflector**  
 2 x LED MODULE **3000K** CRI90 3636lm 28W  
 (on request 2700K CRI90 3456lm)  
 (on request 4000K CRI80 4456lm)  
 220V-240Vac 50/60Hz  
**Dimmable DALI 2 / PUSH**  
 Adjustable  $\pm 15^\circ$  optic

Microslot





**S.3817W Flood beam with reflector**  
 LED MODULE **3000K** CRI90 657lm 6,6W  
 (on request 2700K CRI90 627lm)  
 (on request 4000K CRI80 837lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable  
 Adjustable  $\pm 15^\circ$  optic

Minislot



**S.3827W Flood beam with reflector**  
 LED MODULE **3000K** CRI90 2034lm 15,5W  
 (on request 2700K CRI90 1933lm)  
 (on request 4000K CRI80 2493lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable  
 Adjustable  $\pm 15^\circ$  optic

Slot



**S.3837W Flood beam with reflector**  
 LED MODULE **3000K** CRI90 3636lm 28W  
 (on request 2700K CRI90 3456lm)  
 (on request 4000K CRI80 4456lm)  
 220V-240Vac 50/60Hz  
**Dimmable DALI 2 / PUSH**  
 Adjustable  $\pm 15^\circ$  optic



