





# Stage round


## Ceiling mounted Downlight

This minimal and versatile downlight range comes from the Stage Round projector family. Available in four different sizes, these simple cylindrical objects are equipped with comfortable optics and ensure extremely high performance, both in terms of quality and light emission.

Stage Round for ceiling applications is easy to install and it fits discreetly in all cases where recessed solutions are not suitable.



red dot award 2019  
winner



[www.simes.it/stageround](http://www.simes.it/stageround)



Private villa, Italy - Arch. Duilio Damilano © ph. Mario Bertani

## STAGE ROUND Ceiling mounted Downlight

Die-cast EN AB-47100 aluminium housing with high corrosion resistance.  
 Stainless steel screws.  
 99.98% pure aluminium reflectors.  
 Clear toughened glass diffuser.  
 Luminaire supplied with 5m of cable (Microstage).  
 Luminaire supplied with 3m of cable (Ministage).  
 Pre-wired luminaire with neoprene cable and connector (Stage and Megastage).  
 Silicone gaskets.  
**Double powder paint.**

**Protection class**  
 IP66

**Isolation class**  
 CLASS II

**Mechanical resistance**  
 IK 07 MICRO / MINISTAGE ROUND  
 IK 08 STAGE / MEGA ROUND

Leds 4000K CRI90 versions are available on request.



**S.5506**

4 way connector for through wiring (in/out) only for ceiling versions of Megastage



*For the latest technical information and luminaire updates with LED technology please refer to the official website ([www.simes.it](http://www.simes.it))*

**Colours:**

- White (code 01)
- Aluminium grey (code 14)

**REGISTERED DESIGN**

## Microstage round ceiling





### S.1405W

1 COB LED **3000K** CRI90 350lm  
 Rated luminaire luminous flux 284lm  
 Rated input power 4,3W  
 220V-240V AC 50/60Hz / DC Not Dimmable

h(m)	34° Ø(m)	3000K E(lx)
1	0.62	643
2	1.23	161
3	1.85	71
4	2.46	40
5	3.08	26


## Mnistage round ceiling



### S.1415W

1 COB LED **3000K** CRI90 1225lm  
 Rated luminaire luminous flux 1040lm  
 Rated input power 11,2W  
 220V-240V AC 50/60Hz / DC Not Dimmable

h(m)	27° Ø(m)	3000K E(lx)
1	0.49	3453
2	0.98	863
3	1.46	384
4	1.95	216
5	2.44	64





### S.1416W

1 COB LED **3000K** CRI90 1225lm  
 Rated luminaire luminous flux 1074lm  
 Rated input power 11,2W  
 220V-240V AC 50/60Hz / DC Not Dimmable

h(m)	58° Ø(m)	3000K E(lx)
1	1.10	1221
2	2.20	305
3	3.30	136
4	4.40	76
5	5.50	49


## Stage round ceiling



### S.1425W

1 COB LED **3000K** CRI90 4290lm  
 Rated luminaire luminous flux 3095lm  
 Rated input power 37W  
 220V-240V AC 50/60Hz / DC Not Dimmable

h(m)	30° Ø(m)	3000K E(lx)
2	1.06	2748
4	2.11	687
6	3.17	305
8	4.23	172
10	5.28	110





### S.1426W

1 COB LED **3000K** CRI90 4290lm  
 Rated luminaire luminous flux 3118lm  
 Rated input power 37W  
 220V-240V AC 50/60Hz / DC Not Dimmable

h(m)	58° Ø(m)	3000K E(lx)
2	2.22	939
4	4.43	235
6	6.65	104
8	8.87	59
10	11.09	38


## Megastage round ceiling



### S.1435W

1 COB LED **3000K** CRI90 6700lm  
 Rated luminaire luminous flux 5400lm  
 Rated input power 62,5W  
 220V-240V AC 50/60Hz / DC Not Dimmable  
 Computer-simulated photometrics

h(m)	30° Ø(m)	3000K E(lx)
2	1.06	4795
4	2.11	1199
6	3.17	533
8	4.23	300
10	5.28	192



### S.1436W

1 COB LED **3000K** CRI90 6700lm  
 Rated luminaire luminous flux 5400lm  
 Rated input power 62,5W  
 220V-240V AC 50/60Hz / DC Not Dimmable  
 Computer-simulated photometrics

h(m)	58° Ø(m)	3000K E(lx)
2	2.22	1624
4	4.43	406
6	6.65	180
8	8.87	102
10	11.09	65