

## STAGE ROUND Ceiling surface mounted

SIMES



## STAGE ROUND

Stage Round is a surface mounted downlight extremely minimal in its design and versatile. Available in four different sizes, Stage Round is equipped with comfortable aluminium double inner optics avoiding glare and granting high performance. Stage Round is easy to install and it fits discreetly both in residential and public ambiances.

### TECHNICAL DESCRIPTION

Die-cast aluminium housing with high corrosion resistance. Stainless steel A4 screws. Aluminium reflectors with double inner. Clear toughened glass diffuser. Silicone gaskets. Double powder paint.

### MICROSTAGE

Luminaire pre-wired with 5,0m neoprene H05RN-F cable.

### MINISTAGE

Luminaire pre-wired with 3,0m neoprene H05RN-F cable.

### STAGE AND MEGASTAGE

Luminaire pre-wired with neoprene H05RN-F cable and connector.

### REGISTERED DESIGN

PROTECTION CLASS  
IP66

ISOLATION CLASS  
CLASS II □

MECHANICAL RESISTANCE  
IK 06 MICROSTAGE ROUND  
IK 07 MINISTAGE ROUND  
IK 08 STAGE  
IK 09 MEGASTAGE ROUND

### COLOURS

.01 White



.09 Black

.14 Aluminium Grey





[www.simes.it/stage-round-downlight](http://www.simes.it/stage-round-downlight)

Microstage round




**S.1405W Flood beam with reflector**  
 LED MODULE **3000K** CRI90 356lm 3,0W  
 (on request 2700K CRI90 339lm)  
 (on request 4000K CRI80 454lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable

Mnistage round





**S.1415W Medium beam with reflector**  
 LED MODULE **3000K** CRI90 1251lm 9,5W  
 (on request 2700K CRI90 1195lm)  
 (on request 4000K CRI80 1544lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable




**S.1416W Wide Flood beam with reflector**  
 LED MODULE **3000K** CRI90 1251lm 9,5W  
 (on request 2700K CRI90 1195lm)  
 (on request 4000K CRI80 1544lm)  
 220V-240Vac 50/60Hz  
 ON/OFF Not Dimmable

Stage round





**S.1425W Flood beam with reflector**  
 LED MODULE **3000K** CRI90 4028lm 31,1W  
 (on request 2700K CRI90 3829lm)  
 (on request 4000K CRI80 4936lm)  
 220V-240Vac 50/60Hz  
**Dimmable DALI 2 / PUSH**




**S.1426W Wide Flood beam with reflector**  
 LED MODULE **3000K** CRI90 4028lm 31,1W  
 (on request 2700K CRI90 3829lm)  
 (on request 4000K CRI80 4936lm)  
 220V-240Vac 50/60Hz  
**Dimmable DALI 2 / PUSH**

Megastage round



**S.1435W Flood beam with reflector**  
 LED MODULE **3000K** CRI90 7152lm 57,3W  
 (on request 2700K CRI90 6769lm)  
 (on request 4000K CRI80 8749lm)  
 220V-240Vac 50/60Hz  
**Dimmable DALI 2 / PUSH**



**S.1436W Wide Flood beam with reflector**  
 LED MODULE **3000K** CRI90 7152lm 57,3W  
 (on request 2700K CRI90 6769lm)  
 (on request 4000K CRI80 8749lm)  
 220V-240Vac 50/60Hz  
**Dimmable DALI 2 / PUSH**



Private villa, Sondrio - Italy - Arch. Dutilio Damilano © ph. Mario Bertani