


Streamline

Adjustable Projector

Streamline projector has been designed to illuminate with grazing light walls and facades creating a diffused light effect, thanks to its high luminous flux. Streamline's thin and compact shape discreetly talks together with the context in which it integrates. Its comfortable optics along with the dimming device complete the features of this exterior luminaire, that ensures high performances and flexibility in terms of applications.



2018

www.simes.it/streamline



STREAMLINE Adjustable Projector

Die-cast EN AB-47100 aluminium housing with high corrosion resistance.
Clear toughened glass diffuser.
Stainless steel screws.
Luminaire supplied with 1m of cable (Ministreamline).
Luminaire with double cable entry and cable glands (Streamline).
Silicone gaskets.
Double powder paint.

Protection class
IP65

Isolation class
CLASS I Ⓢ

Mechanical resistance
IK 07

Leds 4000K CRI80 versions are available on request.

The sophisticated optics focuses the beam and makes the light comfortable by reducing the direct glare of the light source.




Colour:

Aluminium grey (code 14)

For the latest technical information and luminaire updates with LED technology please refer to www.simes.it

REGISTERED DESIGN



Ministreamline Comfort Optic



S.1245W

HIGH-POWER LEDs **3000K** CRI90 3300lm
 Rated luminaire luminous flux 2399lm
 Rated input power 32,4W
 220V-240V AC 50/60Hz / DC Not Dimmable

h(m)	12° Ø(m)	3000K E(lx)
2	0.40	9974
4	0.80	2493
6	1.20	1108
8	1.60	623
10	2.00	399




S.1246W

HIGH-POWER LEDs **3000K** CRI90 3300lm
 Rated luminaire luminous flux 2228lm
 Rated input power 32,4W
 220V-240V AC 50/60Hz / DC Not Dimmable

h(m)	31° Ø(m)	3000K E(lx)
2	1.18	1579
4	2.35	395
6	3.53	175
8	4.71	99
10	5.89	63

**Beam lenses available on request with no surcharge:
 66° and 10°x40°**

Ministreamline Asymmetric Optic




S.1247W

MID-POWER LEDs **3000K** CRI80 2880lm
 Rated luminaire luminous flux 1806lm
 Rated input power 20,3W
 220V-240V AC 50/60Hz / DC Not Dimmable

h(m)	E(lx)			
5	1	1	1	0
4	2	2	1	0
3	6	5	2	1
2	22	13	4	1
1	199	34	2	0
0	0	1	2	3 (m)



Streamline Comfort Optic



S.1255W

HIGH-POWER LEDs **3000K** CRI90 7920lm
 Rated luminaire luminous flux 5235lm
 Rated input power 74W
 220V-240V AC 50/60Hz / DC Not Dimmable

h(m)	12° Ø(m)	3000K E(lx)
2	0.41	20415
4	0.81	5104
6	1.22	2268
8	1.63	1276
10	2.03	817




S.1256W

HIGH-POWER LEDs **3000K** CRI90 7920lm
 Rated luminaire luminous flux 4904lm
 Rated input power 74W
 220V-240V AC 50/60Hz / DC Not Dimmable

h(m)	31° Ø(m)	3000K E(lx)
2	1.12	3639
4	2.25	910
6	3.37	404
8	4.50	227
10	5.62	146

**Beam lenses available on request with no surcharge:
 66° and 10°x40°**

Streamline Asymmetric Optic



S.1257W

MID-POWER LEDs **3000K** CRI80 7200lm
 Rated luminaire luminous flux 4274lm
 Rated input power 59W
 220V-240V AC 50/60Hz / DC Not Dimmable

h(m)	E(lx)			
5	2	2	1	1
4	3	3	2	1
3	7	7	4	2
2	28	18	6	2
1	200	55	5	1
0	0	1	2	3 (m)