



Tonight

Bollard

Tonight is a bollard with an essential design particularly suitable for more urban project applications. It is characterised by a very slim pole head where the glass is positioned horizontally to protect the optical group that is totally hidden from sight.

The opal prismatic glass results in a very uniform light distribution, whilst the milled diffuser absorbs any stray light to reduce glare and assure good visual comfort.

Tonight has been developed in two variants, 180° and 360° light distribution.

Tonight was developed in two different dimensions and with two lighting distributions (180° and 360°), all available in two temperatures color (2700K and 3000K).






TONIGHT Bollard

Extruded EN AW-6060 aluminium profile,
Die-cast EN AB-47100 aluminium
housing with high corrosion resistance.
Micro etched prismatic glass diffuser.
Stainless steel screws.
Pre-wired luminaire with neoprene cable
and connector.
Silicone gaskets.
Double powder paint.

Protection class
IP65

Isolation class
CLASS II 


Mechanical resistance
IK 09


Leds 4000K CRI90 versions are available
on request

*For the latest technical information and
luminaire updates with LED technology
please refer to
www.simes.it*

**PATENT PENDING
REGISTERED DESIGN**

Colour:

 Anthracite grey (code .24)






S.4219 FLANGE FOR SAFETY BOLLARD Suitable for TONIGHT 200.

Resistant to vehicle impact of 3500Kg up to max
speed of 50km/h. Steel flange h 500mm to be
cemented in ground. Rooted 500mm into reinforced
concrete plinth 1200x1200x1000mm (the flange
must be welded to the plinth's rebar).



S.5506 4 way connector for through wiring (in/out)



Ø 200

**S.2110W**

MID-POWER LED **3000K** CRI90 1648lm
 Rated luminaire luminous flux 300lm
 Rated input power 12W
 220V-240V AC 50/60Hz / DC
 Not Dimmable




S.2110H

MID-POWER LED **2700K** CRI90 1648lm
 Rated luminaire luminous flux 300lm
 Rated input power 12W
 220V-240V AC 50/60Hz / DC
 Not Dimmable

**S.4171****FLANGE FOR TONIGHT Ø 200mm**

Flange to be fixed in concrete with stainless steel screws for fixing in the ground.



Ø 250

**S.2115W**

MID-POWER LED **3000K** CRI90 2883lm
 Rated luminaire luminous flux 548lm
 Rated input power 22W
 220V-240V AC 50/60Hz / DC DALI
 Computer-simulated photometrics




S.2115H

MID-POWER LED **2700K** CRI90 2883lm
 Rated luminaire luminous flux 548lm
 Rated input power 22W
 220V-240V AC 50/60Hz / DC DALI
 Computer-simulated photometrics

**S.2119****FLANGE FOR TONIGHT Ø 250mm**

Flange to be fixed in concrete with stainless steel screws for fixing in the ground.

Ø 200





S.2111W

MID-POWER LED **3000K** CRI90 3360lm
Rated luminaire luminous flux 640lm
Rated input power 28,1W
220V-240V AC 50/60Hz / DC
Not Dimmable

S.2111H

MID-POWER LED **2700K** CRI90 3360lm
Rated luminaire luminous flux 640lm
Rated input power 28,1W
220V-240V AC 50/60Hz / DC
Not Dimmable





S.4171

FLANGE FOR TONIGHT Ø 200mm

Flange to be fixed in concrete with stainless steel screws for fixing in the ground.

Ø 250





S.2116W

MID-POWER LED **3000K** CRI90 5767lm
Rated luminaire luminous flux 1095lm
Rated input power 44,1W
220V-240V AC 50/60Hz / DC DALI
Computer-simulated photometrics

S.2116H

MID-POWER LED **2700K** CRI90 5767lm
Rated luminaire luminous flux 1095lm
Rated input power 44,1W
220V-240V AC 50/60Hz / DC DALI
Computer-simulated photometrics



S.2119

FLANGE FOR TONIGHT Ø 250mm

Flange to be fixed in concrete with stainless steel screws for fixing in the ground.

