






# Zip Downlight

ZIP DOWNLIGHT is a range of ceiling-recessed light fittings available in square and round versions, supplied with traditional and LED light sources that allow for diverse applications. This range of products is the right answer to any architectural need, both functional lighting and accent lighting.





Virgin Active, Brescia, Arch. Franco Scaglia © Ottavio Tomasini

## ZIP DOWNLIGHT


Die-cast EN AB-44100 aluminium housing (copper free) with high corrosion resistance.  
 Marine grade stainless steel AISI 316L front trim 2 mm thick.  
 Toughened glass diffuser  
 8mm thick for MICROZIP,  
 8mm thick for MINIZIP,  
 10mm thick for ZIP,  
 12mm thick for MEGAZIP.  
 Stainless steel screws.  
 Luminaire hard wired with single neoprene cable (MICROZIP).  
 Luminaire suitable for single cable gland (MINIZIP).  
 Luminaire suitable for double cable glands (ZIP and MEGAZIP).  
 Silicone gaskets.  
**Double powdered paint.**

### Finishing:

○ Stainless steel (code 19)

**Protection class**  
IP65

**Isolation class**  
CLASS I ⊕

**Mechanical resistance of diffuser**  
IK 09  


**Lamps HIT and TC included.**

*For the latest technical information and product updates with LED technology please refer to the official website ([www.simes.it](http://www.simes.it))*



**RECESSING** box for installation in concrete ceilings.

**S.5508**

**MICROZIP ROUND**  
Dimensions: Ø 80÷124 mm h 110 mm

**S.5510**

**MINIZIP ROUND**  
Dimensions: Ø 121÷165 mm h 135 mm

**S.5520**

**ZIP ROUND**  
Dimensions: Ø 190 mm h 240 mm

**S.5530**

**MEGAZIP ROUND**  
Dimensions: Ø 260 mm h 245 mm



**RECESSING** box for installation in concrete ceilings.

**S.5509**

**MICROZIP SQUARE**  
Dimensions: □ 80÷124 mm h 110 mm

**S.5511**

**MINIZIP SQUARE**  
Dimensions: □ 121÷165 mm h 135 mm



**S.5521**

**ZIP SQUARE**  
Dimensions: □ 190 mm h 240 mm

**S.5531**

**MEGAZIP SQUARE**  
Dimensions: □ 260 mm h 245 mm

## Semiacid - etched glass



### S.5831W.19

With 1 led white **3000K** CRI90 105lm  
Rated luminaire luminous flux 91lm



### S.5831N.19

With 1 led white **4000K** CRI90 115lm  
Rated luminaire luminous flux 98lm

Rated input power 2,2W 230V  
Adjustable ±15° optic

h(m)	38° Ø(m)		3000K E(lx)	4000K E(lx)
	1	0.69	191	206
2	1.39	48	52	
3	2.08	21	23	
4	2.77	12	13	
5	3.46	8	8	

## Semiacid - etched glass



### S.5832W.19

With 1 led white **3000K** CRI90 105lm  
Rated luminaire luminous flux 91lm

### S.5832N.19



With 1 led white **4000K** CRI90 115lm  
Rated luminaire luminous flux 98lm

Rated input power 2,2W 230V  
Adjustable ±15° optic

h(m)	38° Ø(m)		3000K E(lx)	4000K E(lx)
	1	0.69	191	206
2	1.39	48	52	
3	2.08	21	23	
4	2.77	12	13	
5	3.46	8	8	

# MINIZIP DOWNLIGHT

## Semiacid - etched glass



### S.5882W.19

With 3 led white **3000K** CRI90 425lm  
Rated luminaire luminous flux 288lm




### S.5882N.19

With 3 led white **4000K** CRI90 460lm  
Rated luminaire luminous flux 317lm

Rated input power 6W 230V  
Adjustable ±15° optic

h(m)	33° Ø(m)		3000K E(lx)	4000K E(lx)
	1	0.58	796	860
2	1.17	199	215	
3	1.75	88	96	
4	2.34	50	54	
5	2.92	32	34	

## Semiacid - etched glass



### S.5892W.19

With 3 led white **3000K** CRI90 425lm  
Rated luminaire luminous flux 288lm



### S.5892N.19

With 3 led white **4000K** CRI90 460lm  
Rated luminaire luminous flux 317lm

Rated input power 6W 230V  
Adjustable ±15° optic

h(m)	33° Ø(m)		3000K E(lx)	4000K E(lx)
	1	0.58	796	860
2	1.17	199	215	
3	1.75	88	96	
4	2.34	50	54	
5	2.92	32	34	


## Acid - etched glass



### S.5843.19

With lamp TC-TEL 18W Gx24q-2 1200lm  
 Rated luminaire luminous flux 348lm  
 Rated input power 22W 230V  
 Lamp position fixed

h(m)	70°	
	Ø(m)	E(lx)
1	1.41	205
2	2.82	51
3	4.23	23
4	5.64	13
5	7.05	8



### S.5883W.19

With leds white **3000K** CRI90 560lm  
 Rated luminaire luminous flux 60lm


h(m)	92°		3000K E(lx)	4000K E(lx)
	Ø(m)			
1	2.07		27	29
2	4.14		7	7
3	6.21		3	3
4	8.28		2	2
5	10.38		1	1

### S.5883N.19

With leds white **4000K** CRI90 605lm  
 Rated luminaire luminous flux 66lm

Rated input power 16W 230V  
 Led position fixed  
 Computer-simulated photometrics

## Semiacid - etched glass



### S.5852W.19

With leds white **3000K** CRI90 1180lm  
 Rated luminaire luminous flux 781lm



h(m)	39°		3000K E(lx)	4000K E(lx)
	Ø(m)			
1	0.70		1562	1687
2	1.40		391	422
3	2.10		174	187
4	2.80		98	105
5	3.50		62	67

### S.5852N.19

With leds white **4000K** CRI90 1275lm  
 Rated luminaire luminous flux 843lm

Rated input power 16W 230V  
 Adjustable ±15° optic


## Acid - etched glass



### S.5863.19

With lamp TC-TEL 18W Gx24q-2 1200lm  
 Rated luminaire luminous flux 348lm  
 Rated input power 22W 230V  
 Lamp position fixed

h(m)	70°	
	Ø(m)	E(lx)
1	1.41	205
2	2.82	51
3	4.23	23
4	5.64	13
5	7.05	8



### S.5893W.19

With leds white **3000K** CRI90 560lm  
 Rated luminaire luminous flux 60lm


h(m)	92°		3000K E(lx)	4000K E(lx)
	Ø(m)			
1	2.07		27	29
2	4.14		7	7
3	6.21		3	3
4	8.28		2	2
5	10.38		1	1

### S.5893N.19

With leds white **4000K** CRI90 605lm  
 Rated luminaire luminous flux 66lm

Rated input power 16W 230V  
 Led position fixed  
 Computer-simulated photometrics

## Semiacid - etched glass



### S.5872W.19

With leds white **3000K** CRI90 1180lm  
 Rated luminaire luminous flux 781lm

h(m)	39°		3000K E(lx)	4000K E(lx)
	Ø(m)			
1	0.70		1562	1687
2	1.40		391	422
3	2.10		174	187
4	2.80		98	105
5	3.50		62	67


### S.5872N.19

With leds white **4000K** CRI90 1275lm  
 Rated luminaire luminous flux 843lm

Rated input power 16W 230V  
 Adjustable ±15° optic




## Acid - etched glass



### S.5573.19

With lamp HIT-CRI 70W G12 6600lm  
 Rated luminaire luminous flux 3533lm  
 Rated input power 84W 230V  
 Adjustable  $\pm 15^\circ$  optic  
 (On request with HIT-CRI 150W G12)

h(m)	43°	
	Ø(m)	E(lx)
2	1.58	1122
4	3.15	281
6	4.73	125
8	6.30	70
10	7.88	45




### S.5574.19

With lamp TC-TEL 26W Gx24q-3 1800lm  
 Rated luminaire luminous flux 558lm  
 Rated input power 31W 230V  
 Lamp position fixed

h(m)	85°	
	Ø(m)	E(lx)
1	1.83	223
2	3.65	56
3	5.48	25
4	7.31	14
5	9.13	9

## Semiacid - etched glass




### S.5578.19

With lamp HIT-CRI 70W G12 6600lm  
 Rated luminaire luminous flux 4934lm  
 Rated input power 84W 230V  
 Adjustable  $\pm 15^\circ$  optic  
 (On request with HIT-CRI 150W G12)

h(m)	19°	
	Ø(m)	E(lx)
2	0.64	5744
4	1.28	1436
6	1.92	638
8	2.56	359
10	3.20	230

## Semiacid - etched glass



### S.5570W.19


With leds white **3000K** CR190 2125lm  
 Rated luminaire luminous flux 1280lm

### S.5570N.19


With leds white **4000K** CR190 2295lm  
 Rated luminaire luminous flux 1382lm


Rated input power 27W 230V  
 Adjustable  $\pm 15^\circ$  optic

h(m)	39° Ø(m)	3000K	4000K
		E(lx)	E(lx)
2	1.43	610	659
4	2.86	153	165
6	4.30	68	73
8	5.73	38	41
10	7.16	24	26




## Acid - etched glass



**S.5593.19**   
 With lamp HIT-CRI 70W G12 6600lm  
 Rated luminaire luminous flux 3533lm  
 Rated input power 84W 230V  
 Adjustable  $\pm 15^\circ$  optic  
 (On request with HIT-CRI 150W G12)


h(m)	43°	
	Ø(m)	E(lx)
2	1.58	1122
4	3.15	281
6	4.73	125
8	6.30	70
10	7.88	45



**S.5594.19**   
 With lamp TC-TEL 26W Gx24q-3 1800lm  
 Rated luminaire luminous flux 558lm  
 Rated input power 31W 230V  
 Lamp position fixed

h(m)	85°	
	Ø(m)	E(lx)
1	1.83	223
2	3.65	56
3	5.48	25
4	7.31	14
5	9.13	9


## Semiacid - etched glass





**S.5598.19**   
 With lamp HIT-CRI 70W G12 6600lm  
 Rated luminaire luminous flux 4934lm  
 Rated input power 84W 230V  
 Adjustable  $\pm 15^\circ$  optic  
 (On request with HIT-CRI 150W G12)

h(m)	19°	
	Ø(m)	E(lx)
2	0.64	5744
4	1.28	1436
6	1.92	638
8	2.56	359
10	3.20	230

## Semiacid - etched glass



**S.5590W.19**   
 With leds white **3000K** CRI90 2125lm  
 Rated luminaire luminous flux 1280lm  
**S.5590N.19**   
 With leds white **4000K** CRI90 2295lm  
 Rated luminaire luminous flux 1382lm

h(m)	39° Ø(m)	3000K	4000K
		E(lx)	E(lx)
2	1.43	610	659
4	2.86	153	165
6	4.30	68	73
8	5.73	38	41
10	7.16	24	26

Rated input power 27W 230V  
 Adjustable  $\pm 15^\circ$  optic

