

Walker / Marker

SIMES

SEGNAPASSO DA INCASSO Step light wall recessed



L.310 D.86 H.65



L.310 D.86 H.65






DESCRIZIONE TECNICA Technical description	INFORMAZIONI GENERALI General information		CODICI COLORE Colour codes
Struttura in alluminio pressofuso. Diffusore in vetro temprato acidato extrachiaro. Viti in acciaio con rivestimento anticorrosivo. Entrata doppia per cavi di alimentazione. Die-cast aluminium housing. Extra-clear acid-etched toughened glass diffuser. Steel screws with anticorrosive coating. Double entry for power cables.	GRADO DI PROTEZIONE IP rating	IP65	●.09 Nero Black ●.14 Grigio alluminio Aluminium Grey
	CLASSE DI ISOLAMENTO Insulation class	CLASS I ⚡	
	RESISTENZA IMPATTO Mechanical resistance	IK 10	

SEGNAPASSO DA INCASSO

Step light wall recessed

WALKER L310



CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
S.6320H	2700 K		90	421 lm	8.8 W	220-240 Vac	Dali2/Push
S.6320W	3000 K		90	433 lm	8.8 W	220-240 Vac	Dali2/Push
S.6320N	4000 K		90	449 lm	8.8 W	220-240 Vac	Dali2/Push


ACCESSORI PER WALKER Accessories for Walker

S.6329 Cassaforma per Walker Recessing box for Walker

SEGNAPASSO DA INCASSO (alzata gradini)

Step light wall recessed (stair riser)

MARKER L310



CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
S.6325H	2700 K		80	107 lm	7.9 W	220-240 Vac	ON-OFF
S.6325W	3000 K		80	113 lm	7.9 W	220-240 Vac	ON-OFF
S.6325N	4000 K		80	117 lm	7.9 W	220-240 Vac	ON-OFF

ACCESSORI PER MARKER Accessories for Marker

S.6329 Cassaforma per Marker Recessing box for Marker