

PARETE Wall mounted



L.90 H.220 D.33



L.220 H.33 D.80

PALETTO Bollard



L.220 H.580 D.33



L.220 H.220 D.33



L.220 H.580 D.66



L.220 H.220 D.66

SEGNAPASSO DA SUPERFICIE Step light surface mounted



L.200 H.200 D.33



L.270 H.115 D.35



L.60 H.115 D.31






DESCRIZIONE TECNICA Technical description	INFORMAZIONI GENERALI General information		CODICI COLORE Colour codes
Struttura in alluminio pressofuso. Rivestimento in legno TEAK. Diffusore in vetro temprato acidato extrachiaro. Viti in acciaio con rivestimento anticorrosivo. Miniskill, Look e Cool precablati con cavo. Skill predisposto per entrata cavo doppia. Die-cast aluminium housing. TEAK wood finish. Extra-clear acid-etched toughened glass diffuser. Steel screws with anticorrosive coating. Pre-wired Miniskill, Look and Cool. Supplied with double cable entry for Skill.	GRADO DI PROTEZIONE IP rating	IP 54 (Cool)	.01 Bianco (rivestimento legno TEAK) White (with TEAK wood finish)
		CLASSE DI ISOLAMENTO Insulation class	
	CLASS I ☹ (Skill)		.20 Bronzo brunito (rivestimento legno TEAK) Burnished bronze (with TEAK wood finish) Materiale soggetto ad invecchiamento naturale. Natural ageing material.
	CLASS II ☹ (Look, Cool)		
	CLASS III ⚡ (Miniskill)		
	RESISTENZA IMPATTO Mechanical resistance	IK 06 (Look, Cool)	BREVETTATO Patented
IK 08 (Skill)			

LOOK LEGNO PARETE

Look Wood wall mounted


MINILOOK APPLIQUE LEGNO SINGOLA EMISSIONE L220

Minilook applique wood single emission L220

	CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	L.9201H	2700 K		90	798 lm	8.8 W	220-240 Vac	Dali2/Push
	L.9201W	3000 K		90	820 lm	8.8 W	220-240 Vac	Dali2/Push
	L.9201N	4000 K		90	851 lm	8.8 W	220-240 Vac	Dali2/Push

MINILOOK APPLIQUE LEGNO DOPPIA EMISSIONE L220

Minilook applique wood double emission L220


	CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	L.9202H	2700 K		90	842 lm	8.8 W	220-240 Vac	Dali2/Push
	L.9202W	3000 K		90	866 lm	8.8 W	220-240 Vac	Dali2/Push
	L.9202N	4000 K		90	898 lm	8.8 W	220-240 Vac	Dali2/Push

LOOK LEGNO PALETTO

Look Wood bollard

MINILOOK PALETTO LEGNO H220


Minilook bollard wood H220

	CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	L.9206H	2700 K		90	798 lm	8.6 W	220-240 Vac	Dali2/Push
	L.9206W	3000 K		90	820 lm	8.6 W	220-240 Vac	Dali2/Push
	L.9206N	4000 K		90	851 lm	8.6 W	220-240 Vac	Dali2/Push

MINILOOK PALETTO LEGNO H580

Minilook bollard wood H580

	CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	L.9211H	2700 K		90	798 lm	8.6 W	220-240 Vac	Dali2/Push
	L.9211W	3000 K		90	820 lm	8.6 W	220-240 Vac	Dali2/Push
	L.9211N	4000 K		90	851 lm	8.6 W	220-240 Vac	Dali2/Push



ACCESSORI PER TUTTE LE VERSIONI DI MINILOOK PALETTO LEGNO

Accessories for all Minilook bollard wood versions

S.7249 Flangia da interrare per Minilook paletto legno Flange to be buried for Minilook bollard wood




COOL LEGNO PARETE

Cool Wood wall mounted

MINICOOL APPLIQUE LEGNO H220

Minilook applique wood H220




CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
L.9231H	2700 K		90	890 lm	8.9 W	220-240 Vac	Dali2/Push
L.9231W	3000 K		90	915 lm	8.9 W	220-240 Vac	Dali2/Push
L.9231N	4000 K		90	949 lm	8.9 W	220-240 Vac	Dali2/Push

COOL LEGNO PALETTO

Cool Wood bollard

MINICOOL PALETTO LEGNO H220


Minicool bollard wood H220




CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
L.9236H	2700 K		90	890 lm	8.9 W	220-240 Vac	Dali2/Push
L.9236W	3000 K		90	915 lm	8.9 W	220-240 Vac	Dali2/Push
L.9236N	4000 K		90	949 lm	8.9 W	220-240 Vac	Dali2/Push

MINICOOL PALETTO LEGNO H580

Minicool bollard wood H580



CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
L.9241H	2700 K		90	890 lm	8.9 W	220-240 Vac	Dali2/Push
L.9241W	3000 K		90	915 lm	8.9 W	220-240 Vac	Dali2/Push
L.9241N	4000 K		90	949 lm	8.9 W	220-240 Vac	Dali2/Push



ACCESSORI PER TUTTE LE VERSIONI DI MINICOOL PALETTO LEGNO

Accessories for all Minicool bollard wood versions

S.7249 Flangia da interrare per Minicool paletto legno Flange to be buried for Minicool bollard wood



SKILL LEGNO SEGNAPASSO DA SUPERFICIE

Skill Wood step light surface mounted

SIMES

MINISKILL SEGNAPASSO VERTICALE LEGNO L60

Miniskill step light vertical wood L60

	CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	L.9230H	2700 K		90	199 lm	4.8 W	24Vdc remote (p.554)	PWM
	L.9230W	3000 K		90	237 lm	4.8 W	24Vdc remote (p.554)	PWM
	L.9230N	4000 K		90	237 lm	4.8 W	24Vdc remote (p.554)	PWM

SKILL SEGNAPASSO QUADRATO LEGNO Ø 200

Skill step light square wood Ø 200

	CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	L.9260H	2700 K		90	521 lm	7.5 W	220-240 Vac	Dali2/Push
	L.9260W	3000 K		90	536 lm	7.5 W	220-240 Vac	Dali2/Push
	L.9260N	4000 K		90	556 lm	7.5 W	220-240 Vac	Dali2/Push

SKILL SEGNAPASSO RETTANGOLARE LEGNO L270

Skill step light rectangular wood L270

	CODE	CCT	BEAM	CRI	FLUX	POWER	POWER SUPPLY	DIMMING
	L.9240H	2700 K		90	601 lm	6.6 W	220-240 Vac	Dali2/Push
	L.9240W	3000 K		90	618 lm	6.6 W	220-240 Vac	Dali2/Push
	L.9240N	4000 K		90	641 lm	6.6 W	220-240 Vac	Dali2/Push