

TECHNICAL DATA SHEET

S.8850.19

ZIP ACCENT LED ROUND

SIMES

luce per l'architettura

-PRODUCT TYPE

Inground walk over fitting .
Recessing depth 240 mm
IP rating IP 67

-MATERIAL CHARACTERISTICS

"Copper Free" Aluminium die cast housing in EN AB 44100 with high resistance against corrosion.

Stone wash surface treatment prior to painting process.

2 mm thick front trim in Stainless Steel - Grade AISI 316L with 2,5-3% molybdenum content.

A4 grade Stainless Steel screws with 2,5-3% molybdenum content which increases the resistance against corrosion.

Pre treated Silicone Gaskets.

Painting Process :

3 Step Process

1) Surface treatment with BONDERITE . A heavy metal free chemical surface treatment containing ceramic nano particles giving a cohesive, inorganic and highly dense protective coating .

2) PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content.

3) POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions. Improved protection for Marine applications.

Mechanical resistance of glass IK 09

Maximum load capacity 1000 Kg

-LIGHTING PERFORMANCE

Toughened semiacid-etched glass 10mm thick.

Lamp adjustable $\pm 15^\circ$ position.

LOR --

-LOW SURFACE TEMPERATURE

Surface temperature of glass 35°C (T_a 15°C)

-RECESSING BOX

Polypropylene recessing box with cable entry on all 4 sides also allows:

1) Easy wiring;

2) Cable management for IP68 fast connector;

3) Easy access to the fitting for maintenance purposes.

-WIRING

Supply cable section type HO7RN-F secured by cable gland PG 13.5 (\varnothing 6÷12 mm) and sealed with B component epoxy resin, wired internally protected by silicon sheaths.

Front re-lamping without removing the complete fitting .


Isolation: CLASS I .

Available colours: STAINLESS STEEL (cod.19).

Weight: 3.58 Kg




Glow Wire test: 850°C


Class 2 L.E.D circuit included. (CEI EN 60825-1:2003-02)




* Photometric measured using COLD WHITE LED 6650K

4 ACCENT LED 6650K 10W 230V
Electronic trasformer 100/240V 50÷60Hz

**IP 67**





FAST CONNECTOR INCLUDED



LAST UPDATE 14/09/2010

SIMES S.p.A.
Via G.Pastore 2/4
25040 - Corte Franca - BRESCIA (ITALY)
<http://www.simes.com> - e-mail: simes@simes.com

Tel:
Export Sales: +39 0309860440
Technical Dep.: +39 0309860450
Lighting Design Dep.: +39 0309860425

Fax:
Export Sales: +39 0309860449
Technical Dep.: +39 0309860459
Lighting Design Dep.: +39 0309860429



The present technical data sheet and all the information contained is property of SIMES S.p.A. All rights reserved.
We reserve the right to change specifications without prior written notice.